

Cod: 6994

## Countertop refrigerated display case curved front glass 130 lt -2 +8°C 900x560x680 h mm



### Description

Ristoattrezzature's **professional counter-top refrigerated display case**, made of **AISI 430 stainless steel** with **AISI 304 stainless steel** profiles, is a machine designed to meet the needs of **pastry shops, supermarkets**, snack bars, sushi bars and all those activities that need to serve their customers cold gastronomy products such as sandwiches, ready-to-eat salads, fruit salads, pastries and cakes, sushi and much more.

The **ventilated cold display case** with internal LED lighting and 130-litre capacity is equipped with two adjustable internal shelves and panoramic curved glass panes to enhance the display space inside: the glass has a double layer of tempered glass so that the positive temperature, adjustable between -2 and +8°C, is effectively maintained by means of a digital device. The rear double-glazed doors are sliding and make opening and closing the display equipment very practical.

### Commissioning the refrigerated display case

Before putting the equipment into operation, following delivery, we recommend that you keep it switched off for at least 6 hours, switch it on and wait until the desired temperature is reached, only then place the food and drinks inside.

## What is refrigeration?

**Refrigeration** is a method of food preservation that involves keeping products at a low temperature, without freezing the water inside the food. To do this, food is kept at a temperature of between 0°C and 10°C. In addition to temperature, the storage environment must also be taken into account, and in particular, humidity: an unsuitable environment can lead to unpleasant consequences such as: loss of product characteristics, development of harmful micro-organisms, withering or browning. Keeping appliance spaces perfectly clean will ensure proper air circulation inside the cells or walls, which is essential for the machinery to function properly.

### Dimensions

Dimensioni esterne	900x560x680 mm
--------------------	----------------

### Technical data

Alimentazione	Electric
Capacità	130 Lt
Classe energetica	C
Compressore	1/3hp, secop dle4.8cn
Frequenza	50 Hz
Gas refrigerante	R290
Peso	70 kg
Potenza Elettrica	0.218 kW
Refrigerazione	ventilated
Ripiani	2 Nr
Temperatura d'esercizio	-2 +8 °C
Termostato	dixell/carel
Voltaggio	230 V

### Standard equipment

In dotazione	2 Griglie totali
--------------	------------------

