

Cod: 85271543013

**Energy-saving refrigerated display case 140,5x33,5x43,5h cm, GN 1/4 0+8°C
pizza trivet with motor on right side**



Description

Speed, precision and quality. The **energy-efficient refrigerated display case** for pizzerias is a valuable aid in the kitchen. Indispensable equipment in the catering sector, it helps you to **better manage your activities and optimise preparation times for your dishes.**

Decide to complete the furnishings of your restaurant with the right element and Ristoattrezzature's display cabinet can really make the difference.

Choose this stand to **keep all the ingredients for filling pizzas at hand, speed up preparation and keep the quality of your products in sight.**

The display case can **accommodate up to 6** easy-to-use **Gastronom trays** for a **truly complete pizza station.**

Let's take a look at the main features together.

Design and operation

The clean and essential design of Ristoattrezzature's **energy-efficient refrigerated display case** allows for easy placement in any environment. **Attention to the quality of the materials** is also of paramount importance when it comes to food and hygiene.

Stainless steel interior and exterior and tough protective glass ensure the product's high quality and durability. The dimensions are **1405x335x435 mm** and can hold 6 standard stainless steel or polycarbonate bowls with or without lids in **GN 1/3 size**.

Choose the one that's right for you by browsing the online catalogue.

The **refrigeration of the pizza display case is static** and is provided by the **integrated motor on the right**. A practical digital display is mounted on the frontal panel from which the operating temperature can be checked.

The latter is **0° C/ + 8° C** and can be easily **adjusted thanks to a Dixell electronic controller** that allows you to adjust the temperature at any time. The gas used for cooling is **R600a refrigerant gas** with an **Embraco, Zanussi compressor**.

The motor has a **frequency of 50 Hz** and a **voltage of 230 V**.

Robustness and professionalism

Rely on Ristoattrezzature's experience and professionalism and choose for your restaurant an **innovative, safe, solid and, above all, compliant** product.

The **refrigerated display case for restaurants** has been designed to guarantee **high performance over time** in different types of premises: **pizzerias, restaurants, sandwich shops, pubs, fast food outlets, etc.**

An attractive investment for a **versatile, quality product**. Choose the ideal location and increase, in a few moves and in a small space, productivity in the kitchen.

Why it is the right product for you

If you want to maintain the high standard of your preparations, you must ensure proper storage for the ingredients that form the basis of your dishes. Choosing the Ristoattrezzature **pizza sauce cabinet** is the first move you should make.

Made of high quality stainless steel, it guarantees high levels of **reliability, performance and style**. Without compromising on excellent value for money. **Efficient performance and low consumption**.

Ristoattrezzature's **energy-efficient refrigerated display case** can perfectly preserve your food even at a **maximum ambient temperature of 32 °C** thanks to the innovative technology employed.

Finally, by purchasing our display cabinet, you will be helping the environment. It uses a **100% natural source** for its operation : **the refrigerant gas R600a**. Read all product details in the data sheet.

Dimensions

| | |
|------------------------|-----------------|
| Dimensioni esterne | 1405x335x435 mm |
| Spessore coibentazione | 40 mm |

Technical data

| | |
|-----------------------------|----------------------|
| Capacità | 40 Lt |
| Capacità/capacità bacinelle | 40 l / bac gn1/4 x 6 |
| Compressore | Hua Yi HYB81MHUa |
| Consumo elettrico | 1.55 Kw/24h |
| Frequenza | 50 Hz |
| Gas refrigerante | R600A |
| Peso | 41 kg |
| Potenza Elettrica | 0.18 kW |
| Refrigerazione | static |
| Sbrinamento | air defrost |
| Temperatura d'esercizio | 0 +8 °C |
| Termostato | dixell/carel |
| Voltaggio | 230 V |