

Cod: 9406

Complete pizzeria



Description

Ristoattrezzature offers "Your Complete Pizzeria" consisting of: 1) Stainless steel ventilated refrigerated pizza counter with 2 doors and 5 drawers size 2070x800x870h mm for restaurant pizzerias. The product has a rounded corner on the bottom for easy cleaning and is equipped with wheels. Self-closing doors. Magnetic gaskets, easy to clean and replace. The refrigerating unit is tropicalised, i.e. it can work in an outdoor environment with a temperature of up to +40°C/42°C and 65% relative humidity. The operating temperature uses a range of 0° C/ + 8° C and can be easily adjusted thanks to a Dixell electronic controller with temperature display. The temperature can also be easily read on a digital thermostat on the front wall of the counter. The counter is equipped with 2 doors fitted with a heating element to eliminate condensation and an easily removable magnetic seal. 2) The Ristoattrezzature spiral mixer offers maximum convenience while guaranteeing optimum performance. It is a product that allows you to make well-blended, lump-free dough. The product has a fixed head and bowl. The mixer has no wheels. 3) Stainless steel refrigerated cabinet 1 door 700 lt, ventilated -2 +8 °C 4) Wall-mounted stainless steel hand-washing unit with knee control. 1 ½" connection is required for water loading. The shape of the basin is spherical and the drain hole is exactly in the centre of the basin. The connections must be made under the wall imprint of the sink. Tap not included. 5) Mechanical electric oven made of

stainless steel and pre-painted sheet metal. Baking shelf made of refractory stone for Ø 32 cm pizzas. Evaporated rock wool insulation. Armoured heating elements. Internal lighting. 6) Refrigerated display case for pizzerias designed to guarantee exceptional performance day after day in all catering areas. Ideal for restaurants, fast food chains, take-away, delicatessens, sandwich shops, etc. Manufactured in high quality stainless steel to ensure a high level of reliability, performance, style and excellent value for money. Stainless steel interior and exterior and protective glass. Compatible with standard deli containers, the refrigerated display case is suitable for holding X GN 1/4 gastronorm trays in stainless steel or polycarbonate. The operating temperature exploits a range of + 2° C/ + 8° C and can be easily adjusted thanks to a Dixell electronic controller with temperature display. Refrigeration is static with R600a refrigerant gas.

In basso la scheda tecnica di ogni prodotto del Kit:

SKU: 5449

Electric pizza oven for mechanical pizza 2 internal chambers 660x660x140h mm - 4+4 pizzas

Dimensions

| | |
|--------------------|----------------|
| Dimensioni esterne | 975x924x745 mm |
| Dimensioni interne | 660x660x140 mm |

Technical data

| | |
|---------------------------|-------------|
| Alimentazione | Electric |
| Peso | 129 kg |
| Potenza Elettrica | 9.4 kW |
| Potenza resistenza cielo | 4.7 kW |
| Potenza resistenza platea | 4.7 kW |
| Temperatura d'esercizio | +50 +500 °C |
| Voltaggio | 400 V |

SKU: 10390072003

Three-phase spiral mixer 33 lt - EC

Dimensions

| | |
|--------------------|----------------|
| Diametro vasca | 400 mm |
| Dimensioni esterne | 440x830x720 mm |
| Dimensioni imballo | 500x910x880 mm |

Technical data

| | |
|---------------------|----------|
| Alimentazione | Electric |
| Capacità | 33 Lt |
| Capacità di Impasto | 25 kg |
| Capacità di Impasto | 100 Kg/h |
| Peso | 110 kg |
| Peso lordo | 133 kg |
| Potenza Elettrica | 1.30 kW |
| Voltaggio | 400 V |

Standard equipment

| | |
|--------------|----------------|
| In dotazione | temporizzatore |
|--------------|----------------|

SKU: 108992671

Wall-mounted stainless steel washbasin 40x33x57h cm with splash guard

Dimensions

| | |
|--------------------|----------------|
| Dimensioni esterne | 400x330x570 mm |
|--------------------|----------------|

SKU: 8645

Stainless steel refrigerated cabinet 1 door 700 lt, ventilated -2 +8 °C tropicalized

Dimensions

| | |
|--------------------|-----------------|
| Dimensioni esterne | 740x830x2010 mm |
| Dimensioni interne | 624x702x1401 mm |

Technical data

| | |
|------------------------------|------------|
| Alimentazione | Electric |
| Capacità | 650 Lt |
| Compressore | embraco |
| Frequenza | 50 Hz |
| Gas refrigerante | R290 |
| Potenza Elettrica | 0.215 kW |
| Refrigerazione | ventilated |
| Temperatura ambiente massima | 43 °C |
| Temperatura d'esercizio | -2 +8 °C |
| Termostato | dixell |

| | |
|-----------|-------|
| Voltaggio | 230 V |
|-----------|-------|

Standard equipment

| | |
|--------------|-----------------|
| In dotazione | 3 griglie GN2/1 |
|--------------|-----------------|

SKU: 88260001006001

Refrigerated display case for condiments, pizza crusts GN 1/4 2000x335x435h mm +2 +8 °C a with energy-saving right-hand motor

Dimensions

| | |
|--------------------|-----------------|
| Dimensioni esterne | 2000x335x435 mm |
|--------------------|-----------------|

Technical data

| | |
|------------------------------|------------------|
| Alimentazione | Electric |
| Capacità vaschette | 10 GN 1/4 |
| Compressore | embraco, zanussi |
| Frequenza | 50 Hz |
| Gas refrigerante | R600A |
| Potenza Elettrica | 0.11 kW |
| Refrigerazione | static |
| Temperatura ambiente massima | 32 °C |
| Temperatura d'esercizio | +2 +8 °C |
| Termostato | dixell |
| Voltaggio | 230 V |

SKU: sb 4-441

Support 975x815x960h mm

SKU: 92070020051660

Pizza counter 2 doors 7 drawers 2025x800x1000 h mm for pizzeria restaurant tropicalised

Dimensions

| | |
|--------------------|------------------|
| Dimensioni esterne | 2025x800x1000 mm |
|--------------------|------------------|

Technical data

| | |
|---------------|----------|
| Alimentazione | Electric |
| | |

| | |
|------------------------------|------------|
| Capacità | 580 Lt |
| Compressore | embraco |
| Frequenza | 50 Hz |
| Gas refrigerante | R290 |
| Potenza Elettrica | 0.215 kW |
| Refrigerazione | ventilated |
| Temperatura ambiente massima | 43 °C |
| Temperatura d'esercizio | -2 +8 °C |
| Termostato | dixell |
| Voltaggio | 230 V |