

Cod: 95560971737016

Ventilated stainless steel refrigerated cabinet 1 door with touch instrument 900 Lt 790x1020x2090h mm -2 +8 °C



Description

The refrigerated cabinet boasts the following features - monobloc with 75 mm insulation with HFO polyurethane foam, which has a GWP level of 0; - the material used is all Aisi 304 both inside and outside except for the top, back and external bottom which are in any case in Aisi 430; - monobloc type units, they use R290 gas (GWP equal to 3) which results in considerable energy savings - hot gas defrosting, and not resistance defrosting, allows energy savings and defrosting is carried out more quickly; - partially ducted ventilation to ensure proper air circulation inside the cold room; - the guides are hand-saving, removable racks - the fan stop micro when opening the door is mechanical and does not need to be moved if the opening direction is changed; - the door is reversible, simply mount the lower hinge on the opposite side; - the interior fittings are the door is reversible, simply mount the lower hinge on the opposite side; - the interior fittings are interlocking and easily removable for ease of cleaning; - the air outlet, in ventilated cabinets, is protected by a channel, which ensures that the cold air outlet is not obstructed by products or ice formations;

Dimensions

Dimensioni esterne	790x1020x2090 mm
--------------------	------------------

Technical data

Alimentazione	Electric
Classe energetica	B
Frequenza	50 Hz
Potenza Elettrica	0.4 kW
Temperatura d'esercizio	-2 +8 °C
Voltaggio	230 V

Standard equipment

In dotazione	16 LIVELLI CON GUIDE A "L" SENZA GRIGLIE PER TEGLIE O PIANI 600X800 PASSO 75
--------------	--