

Cod: 95761753059001

## **Smeg UG420D Topline Series glasswasher with 400x400 mm basket 4.8 kW Standard**



### **Description**

Professional, double-walled, 400 mm basket, detergent dispenser, HTR rinsing system.

This glass washer has a loading height of 300 mm on a total height of 705 mm, allowing even large glasses to be washed.

- Structure: AISI 304 double-walled stainless steel with insulation
- Control panel: touch
- No. of programmes: 9
- Rinse aid dispenser: electronically controlled peristaltic pump
- Detergent dosing unit: electronically controlled peristaltic pump
- Thermal-acoustic insulation: washing chamber
- Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel
- Washing system: Washing pump with 'Soft Start' system
- Drain system: Drain pump for partial drainage of wash water, inspectable
- Filter system: Three-stage filtration integrated with the drain pump for separation of

residues and control of the water level in the tank

- Rinsing system: rinse pump and atmospheric boiler (HTR System)
- TOTAL RINSING' function of the water in the tank after each wash
- EXTRA RINSE' function for prolonged rinsing
- Double-walled, balanced, insulated and gasketed door
- Automatic cycle start at door closure (selectable)
- Double-walled tank with rounded corners
- Insulated boiler
- Crystal cycle with reduced rinse temperature
- ULTRA CLEAN PRO cycle for sanitising dishes
- Selectable 'Drain and clean tank' cycle
- Mains non-return device
- Thermostop for rinsing water temperature control
- Self-diagnosis system with fault indication
- Filter positioning control system
- Heating element 'Stand-by' function during periods of non-use

## Dimensions

Dimensioni cesto	400x400 mm
Dimensioni esterne	460x600x705 mm
Dimensioni imballo	515x710x720 mm

## Technical data

Alimentazione	Electric
Capacità	7 Lt
Capacità boiler	4 Lt
Frequenza	50 Hz
Materiale	aisi 304 stainless steel
Potenza Elettrica	4.8 kW
Resistenza boiler	4.5 kW
Resistenza vasca	2 kW
Temperatura ambiente massima	60 °C
Temperatura ambiente minima	8 °C
Voltaggio	400 V

## Standard equipment

In dotazione	Cesto in filo universale con fondo
--------------	------------------------------------

piano 400x400 mm, Cesto in filo per  
8 calici con fondo inclinato 400x400  
mm e Porta posate singolo in  
polipropilene