

Cod: 95761754060006

# Smeg UG520DSL Topline Series glasswasher with 500x500 mm basket 6.7 kW with softener



## Description

Professional under counter glass washer, double wall, 500mm basket, detergent dispenser, softener

- Structure: double-walled AISI 304 stainless steel with insulation
- Control panel: touch
- No. of programmes: 14
- Hour baskets: 72/60/50/40/30/24/15/3
- Useful load height: 307 mm
- Rinse aid dispenser: electronically controlled peristaltic pump
- Detergent dispenser: electronically controlled peristaltic pump
- Thermal-acoustic insulation: door and washing chamber
- Softener: Integrated
- Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel
- Washing system: Washing pump with 'Soft Start' system

- Washing pump power: 0.7 kW
- Drain system: Drain pump for partial outflow of wash water, inspectable
- Filter system: Three-stage filtration integrated with the drain pump for separation of residues and control of the water level in the tank
- Rinsing system: rinse pump and atmospheric boiler (HTR System)
- Tank heating element: 0.8 kW
- Boiler heating element: 6.00 kW / 2.00 kW single-phase
- TOTAL RINSING' function of the water in the tank after each wash
- EXTRA RINSE' function for prolonged rinsing
- Double-walled, balanced, insulated and gasketed door
- Automatic cycle start when door is closed (selectable)
- Double-walled tank with rounded corners
- Insulated boiler
- Crystal cycle with reduced rinse temperature
- ULTRA CLEAN PRO cycle for sanitising dishes
- Selectable 'Drain and clean tank' cycle
- Mains non-return device
- Thermostop for rinsing water temperature control
- Self-diagnosis system with fault indication
- Filter positioning control system
- Heating element 'Stand-by' function during periods of non-use

#### **Dimensions**

Dimensioni esterne	600x600x720 mm
--------------------	----------------

## **Technical data**

Alimentazione	Electric	
Capacità	11 Lt	
Capacità boiler	6 Lt	
Consumo d'acqua	2.7 kg	
Frequenza	50 Hz	
Materiale	aisi 304 stainless steel	
Potenza Elettrica	6.7 kW	
Voltaggio	230 V, 400 V	

## Standard equipment

In dotazione	Cesto per piatti, max 18 pezzi Ø 250 mm, Cesto universale con fondo piano per 18 piatti, Cestello per posate singolo
	posate singolo