

Cod: 95781754060001

Smeg UD522D Topline Series double basket dishwashers with 500x500 mm baskets 6.7 kW Standard



Description

Professional under counter dishwasher, double 500 mm basket with detergent dispenser
Structure: AISI 304 double-walled stainless steel with insulation Control panel: touch Feature:
Double basket system with removable holder No. of programmes: 14 Hour baskets:
72/60/50/40/30/24/15/3 Basket dimensions: 2 baskets 500x500 mm Useful load height: 415 mm
Rinse aid dispenser: electronically controlled peristaltic pump Detergent dispenser: electronically
controlled peristaltic pump Thermal-acoustic insulation: door and washing chamber
Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel Washing system:
Washing pump with 'Soft Start' system Washing pump power: 0.7 kW Drain system: Drain pump
for partial outflow of wash water, inspectable Filter system: Three-stage filtration integrated with
the drain pump for separation of residues and control of the water level in the tank Rinsing
system: rinse pump and atmospheric boiler (HTR System) Tank heating element: 0.8 kW Boiler
heating element: 6.00 kW / 2.00 kW single-phase Lower basket: for washing cups and glasses
Upper basket - useful loading height: 145 / 225 mm Lower basket - useful loading height: 190 /
110 mm (depending on the positioning of the upper basket) Washing capacity: 2 baskets 500x500
mm, simultaneously Upper basket: for washing dishes and saucers with 2 levels of adjustment

TOTAL RINSING' function of the water in the tank after each wash EXTRA RINSE' function for prolonged rinsing Double wash basket system Double-walled, balanced, insulated and gasketed door Automatic cycle start when door is closed (selectable) Double-walled tank with rounded corners Insulated boiler Crystal cycle with rinse temperature reduction ULTRA CLEAN PRO cycle for sanitising dishes Selectable 'Drain and clean tank' cycle Mains non-return device Thermostop for rinsing water temperature control Self-diagnosis system with fault indication Filter positioning control system Heater stand-by function during periods of non-use Drain pump system Triple-stage filtration system integrated in the drain pump Tank with rounded corners Peristaltic pump detergent dispenser Rinse aid dispenser with peristaltic pump

Dimensions

Dimensioni esterne	600x600x820 mm
--------------------	----------------

Technical data

Alimentazione	Electric
Capacità	11 Lt
Capacità boiler	6 Lt
Consumo d'acqua	2.7 kg
Frequenza	50 Hz
Materiale	aisi 304 stainless steel
Potenza Elettrica	6.7 kW
Voltaggio	230 V, 400 V

Standard equipment

In dotazione	Cesto per piatti, max 18 pezzi Ø 250 mm, Cesto universale con fondo piano, Cestello per posate a 6 scomparti
--------------	--