

Cod: 95781754060006

Smeg UD522DS Topline Series double basket dishwasher with 500x500 mm baskets 6.7 kW with softener



Description

Professional undercounter dishwasher, 500 mm double basket with detergent dosing unit and softener

- Structure: AISI 304 double-walled stainless steel with insulation
- Control panel: touch
- Feature: Double basket system with removable holder
- No. of programmes: 14
- Hour baskets: 72/60/50/40/30/24/15/3
- Basket dimensions: 2 baskets 500x500 mm
- Useful load height: 415 mm
- Rinse aid dispenser: electronically controlled peristaltic pump
- Detergent dispenser: electronically controlled peristaltic pump
- Thermal-acoustic insulation: door and washing chamber
- Softener: Integrated
- Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel

- Washing system: Washing pump with 'Soft Start' system
- Washing pump power: 0.7 kW
- Drain system: Drain pump for partial outflow of wash water, inspectable
- Filter system: Three-stage filtration integrated with the drain pump for separation of residues and control of the water level in the tank
- Rinsing system: rinse pump and atmospheric boiler (HTR System)
- Tank heating element: 0.8 kW
- Boiler heating element: 6.00 kW / 2.00 kW single-phase
- Lower basket: for washing cups and glasses
- Upper basket - useful loading height: 145 / 225 mm
- Lower basket - useful loading height: 190 / 110 mm (depending on the positioning of the upper basket)
- Washing capacity: 2 baskets 500x500 mm, simultaneously
- Upper basket: for washing dishes and saucers with 2 levels of adjustment
- TOTAL RINSING' function of the water in the tank after each wash
- EXTRA RINSE' function for prolonged rinsing
- Double wash basket system
- Double-walled, balanced, insulated and gasketed door
- Automatic cycle start when door is closed (selectable)
- Double-walled tank with rounded corners
- Insulated boiler
- Crystal cycle with rinse temperature reduction
- ULTRA CLEAN PRO cycle for sanitising dishes
- Selectable 'Drain and clean tank' cycle
- Mains non-return device
- Thermostop for rinsing water temperature control
- Self-diagnosis system with fault indication
- Filter positioning control system
- Heater stand-by function during periods of non-use
- Drain pump system
- Triple-stage filtration system integrated in the drain pump
- Tank with rounded corners
- Peristaltic pump detergent dispenser
- Rinse aid dispenser with peristaltic pump

Dimensions

Dimensioni esterne	600x600x820 mm
--------------------	----------------

Technical data

Alimentazione	Electric
Capacità	11 Lt
Capacità boiler	6 Lt
Consumo d'acqua	2.7 kg
Frequenza	50 Hz

Materiale	aisi 304 stainless steel
Potenza Elettrica	6.7 kW
Voltaggio	230 V, 400 V

Standard equipment

In dotazione	Cesto per piatti, max 18 pezzi Ø 250 mm, Cesto universale con fondo piano, Cestello per posate a 6 scomparti
--------------	--