

Cod: 95791754060001

## Smeg UD526D Series Topline washer-dryer with 500x500 mm basket 6.7 kW Standard



### Description

Professional undercounter tray washer, for 600x400mm Euronorm trays and baskets, with detergent dispenser, suitable for washing 600x400mm GN1/1 trays Structure: double-walled AISI 304 stainless steel with insulation Control panel: touch Feature: designed for washing 600x400mm Euronorm pans and baskets No. of programmes: 14 Baskets/hour: 72/60/50/40/30/24/15/3 Basket dimensions: 500x500 mm Useful loading height: 415 mm Rinse aid dispenser: electronically controlled peristaltic pump Detergent dispenser: electronically controlled peristaltic pump Thermal-acoustic insulation: door and washing chamber Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel Washing system: Washing pump with 'Soft Start' system Washing pump power: 0.7 kW Drain system: Drain pump for partial outflow of wash water, inspectable Filter system: Three-stage filtration integrated with the drain pump for separation of residues and control of the water level in the tank Rinsing system: rinse pump and atmospheric boiler (HTR System) Tank heating element: 0.8 kW Boiler heating element: 6.00 kW / 2.00 kW single-phase Useful loading depth: 605 mm Washing capacity: EURONORM 600x400mm trays and EURONORM 600x400 baskets (xH 350mm max) TOTAL RINSING' function of the water in the tank after each wash EXTRA RINSE' function for

prolonged rinsing Euronorm 600x400mm pan and crate washing Double-walled, balanced, insulated and gasketed door Automatic cycle start at door closure (selectable) Double-walled tank with rounded corners Insulated boiler Crystal cycle with reduced rinse temperature ULTRA CLEAN PRO cycle for sanitising dishes Selectable 'Drain and clean tank' cycle Mains non-return device Thermostop for rinsing water temperature control Self-diagnosis system with fault indication Filter positioning control system Heater stand-by function during periods of non-use Drain pump system Triple-stage filtration system integrated in the drain pump Peristaltic pump detergent dispenser Rinse aid dispenser with peristaltic pump

## Dimensions

Dimensioni esterne	600x680x820 mm
--------------------	----------------

## Technical data

Alimentazione	Electric
Capacità	11 Lt
Capacità boiler	6 Lt
Consumo d'acqua	2.7 kg
Frequenza	50 Hz
Materiale	aisi 304 stainless steel
Potenza Elettrica	6.7 kW
Voltaggio	230 V, 400 V

## Standard equipment

In dotazione	Cesto per piatti, max 18 pezzi Ø 250 mm, Cesto in filo per 8 teglie Euronorm 600x400mm, Griglia per cesta Euronorm 600x400x H350mm max, Cesto in filo per teglie GN1/1 prof. 60mm
--------------	---