

Cod: 95791754060006

Smeg UD526DS Topline Series washer-dryer with 500x500 mm basket 6.7 kW with softener



Description

Professional undercounter tray washer, for 600x400mm Euronorm trays and baskets, with detergent dispenser and softener, suitable for washing 600x400mm GN1/1 trays

- Structure: double-walled AISI 304 stainless steel with insulation
- Control panel: touch
- Feature: designed for washing Euronorm 600x400mm pans and baskets
- No. of programmes: 14
- Baskets/hour: 72/60/50/40/30/24/15/3
- Basket dimensions: 500x500 mm
- Useful loading height: 415 mm
- Rinse aid dispenser: electronically controlled peristaltic pump
- Detergent dispenser: electronically controlled peristaltic pump
- Thermal-acoustic insulation: door and washing chamber
- Softener: Integrated
- Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel

- Washing system: Washing pump with 'Soft Start' system
- Washing pump power: 0.7 kW
- Drain system: Drain pump for partial outflow of wash water, inspectable
- Filter system: Three-stage filtration integrated with the drain pump for separation of residues and control of the water level in the tank
- Rinsing system: rinse pump and atmospheric boiler (HTR System)
- Tank heating element: 0.8 kW
- Boiler heating element: 6.00 kW / 2.00 kW single-phase
- Useful loading depth: 605 mm
- Washing capacity: EURONORM 600x400mm trays and EURONORM 600x400 baskets (xH 350mm max)
- TOTAL RINSING' function of the water in the tank after each wash
- EXTRA RINSE' function for prolonged rinsing
- Euronorm 600x400mm pan and crate washing
- Double-walled, balanced, insulated and gasketed door
- Automatic cycle start at door closure (selectable)
- Double-walled tank with rounded corners
- Insulated boiler
- Crystal cycle with reduced rinse temperature
- ULTRA CLEAN PRO cycle for sanitising dishes
- Selectable 'Drain and clean tank' cycle
- Mains non-return device
- Thermostop for rinsing water temperature control
- Self-diagnosis system with fault indication
- Filter positioning control system
- Heater stand-by function during periods of non-use
- Drain pump system
- Triple-stage filtration system integrated in the drain pump
- Peristaltic pump detergent dispenser
- Rinse aid dispenser with peristaltic pump

Dimensions

Dimensioni esterne	600x680x820 mm
--------------------	----------------

Technical data

Alimentazione	Electric
Capacità	11 Lt
Capacità boiler	6 Lt
Consumo d'acqua	2.7 kg
Frequenza	50 Hz
Materiale	aisi 304 stainless steel
Potenza Elettrica	6.7 kW
Voltaggio	230 V, 400 V

Standard equipment

In dotazione	Cesto per piatti, max 18 pezzi Ø 250 mm, Cesto in filo per 8 teglie Euronorm 600x400mm, Griglia per cesta Euronorm 600x400x H350mm max, Cesto in filo per teglie GN1/1 prof. 60mm
--------------	---