

Cod: 95831754060001

Smeg FD520D Topline Series raised dishwasher with 500x500 mm basket 6.7 kW Standard



Description

Professional dishwasher with front loading, raised, 500mm basket, double walled, detergent dispenser Control panel: touch No. of programmes: 14 Hour baskets: 72/60/50/40/30/24/15/3 Basket dimensions: 500x500 mm Useful load height: 415 mm Rinse aid dispenser: electronically controlled peristaltic pump Detergent dispenser: electronically controlled peristaltic pump Thermalacoustic insulation: door and washing chamber Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel Washing system: Washing pump with 'Soft Start' system Washing pump power: 0.7 kW Drain system: Drain pump for partial outflow of wash water, inspectable Filter system: Three-stage filtration integrated with the drain pump for separation of residues and control of the water level in the tank Rinsing system: rinse pump and atmospheric boiler (HTR System) Tank heating element: 0.8 kW Boiler heating element: 6.00 kW / 2.00 kW single-phase Power supply / Maximum power consumption: 400V 3N 50 Hz / 6.8 kW; 230V 3N 50Hz / 6.8 kW; 230V 1N 50Hz / 2.8 kW Bottom compartment size: 560x320mm Weight (net / gross): 80/88 kg TOTAL RINSING' function of the water in the tank after each wash EXTRA RINSE' function for prolonged rinsing Double-walled, balanced, insulated and gasketed door Automatic cycle start at door closure (selectable) Double-walled tank with rounded corners Insulated boiler Crystal cycle

with reduced rinse temperature ULTRA CLEAN PRO cycle for sanitising dishes Selectable 'Drain and clean tank' cycle Mains non-return device Thermostop for rinsing water temperature control Self-diagnosis system with fault indication Filter positioning control system Heating element 'Stand-by' function during periods of non-use

Dimensions

Dimensioni esterne	600x600x1350 mm
--------------------	-----------------

Technical data

Alimentazione	Electric
Capacità	11 Lt
Capacità boiler	6 Lt
Consumo d'acqua	2.7 kg
Frequenza	50 Hz
Materiale	aisi 304 stainless steel
Potenza Elettrica	6.7 kW
Voltaggio	230 V, 400 V

Standard equipment

In dotazione	Cesto per piatti, max 18 pezzi Ø 250 mm, Cesto universale con fondo
	piano per 18 piatti, Cestello per posate a 6 scomparti