

Cod: 95831754060006

Smeg FD520DS Topline Series raised dishwasher with 500x500 mm basket 6.7 kW with softener



Description

Professional dishwasher with front loading, raised, 500mm basket, double walled, detergent dispenser, softener Control panel: touch No. of programmes: 14 Baskets per hour: 72/60/50/40/30/24/15/3 Basket dimensions: 500x500 mm Useful load height: 415 mm Rinse aid dispenser: electronically controlled peristaltic pump Detergent dispenser: electronically controlled peristaltic pump Thermal-acoustic insulation: door and washing chamber Softener: Integrated Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel Washing system: Washing pump with 'Soft Start' system Washing pump power: 0.7 kW Drain system: Drain pump for partial outflow of wash water, inspectable Filter system: Three-stage filtration integrated with the drain pump for separation of residues and control of the water level in the tank Rinsing system: rinse pump and atmospheric boiler (HTR System) Tank heating element: 0.8 kW Boiler heating element: 6.00 kW / 2.00 kW single-phase Power supply / Maximum power consumption: 400V 3N 50 Hz / 6.8 kW; 230V 3N 50Hz / 6.8 kW; 230V 1N 50Hz / 2.8 kW Bottom compartment size: 560x320mm Weight (net / gross): 80/88 kg TOTAL RINSING' function of the water in the tank after each wash EXTRA RINSE' function for prolonged rinsing Double-walled, balanced, insulated and gasketed door Automatic cycle start at door closure (selectable) Double-walled tank

with rounded corners Insulated boiler Crystal cycle with reduced rinse temperature ULTRA CLEAN PRO cycle for sanitising dishes Selectable 'Drain and clean tank' cycle Mains non-return device Thermostop for rinsing water temperature control Self-diagnosis system with fault indication Filter positioning control system Heating element 'Stand-by' function during periods of non-use

Dimensions

Dimensioni esterne	600x600x1350 mm
--------------------	-----------------

Technical data

Alimentazione	Electric
Capacità	11 Lt
Capacità boiler	6 Lt
Consumo d'acqua	2.7 kg
Frequenza	50 Hz
Materiale	aisi 304 stainless steel
Potenza Elettrica	6.7 kW
Voltaggio	230 V, 400 V

Standard equipment

In dotazione	Cesto per piatti, max 18 pezzi Ø 250 mm, Cesto universale con fondo piano per 18 piatti, Cestello per
	posate a 6 scomparti