

Cod: 95831754060006

## **Smeg FD520DS Topline Series raised dishwasher with 500x500 mm basket 6.7 kW with softener**



### **Description**

**Professional dishwasher with front loading, raised, 500mm basket, double walled, detergent dispenser, softener**

- Control panel: touch
- No. of programmes: 14
- Baskets per hour: 72/60/50/40/30/24/15/3
- Basket dimensions: 500x500 mm
- Useful load height: 415 mm
- Rinse aid dispenser: electronically controlled peristaltic pump
- Detergent dispenser: electronically controlled peristaltic pump
- Thermal-acoustic insulation: door and washing chamber
- Softener: Integrated
- Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel
- Washing system: Washing pump with 'Soft Start' system
- Washing pump power: 0.7 kW

- Drain system: Drain pump for partial outflow of wash water, inspectable
- Filter system: Three-stage filtration integrated with the drain pump for separation of residues and control of the water level in the tank
- Rinsing system: rinse pump and atmospheric boiler (HTR System)
- Tank heating element: 0.8 kW
- Boiler heating element: 6.00 kW / 2.00 kW single-phase
- Power supply / Maximum power consumption: 400V 3N 50 Hz / 6.8 kW; 230V 3N 50Hz / 6.8 kW; 230V 1N 50Hz / 2.8 kW
- Bottom compartment size: 560x320mm
- Weight (net / gross): 80/88 kg
- TOTAL RINSING' function of the water in the tank after each wash
- EXTRA RINSE' function for prolonged rinsing
- Double-walled, balanced, insulated and gasketed door
- Automatic cycle start at door closure (selectable)
- Double-walled tank with rounded corners
- Insulated boiler
- Crystal cycle with reduced rinse temperature
- ULTRA CLEAN PRO cycle for sanitising dishes
- Selectable 'Drain and clean tank' cycle
- Mains non-return device
- Thermostop for rinsing water temperature control
- Self-diagnosis system with fault indication
- Filter positioning control system
- Heating element 'Stand-by' function during periods of non-use

## Dimensions

Dimensioni esterne	600x600x1350 mm
--------------------	-----------------

## Technical data

Alimentazione	Electric
Capacità	11 Lt
Capacità boiler	6 Lt
Consumo d'acqua	2.7 kg
Frequenza	50 Hz
Materiale	aisi 304 stainless steel
Potenza Elettrica	6.7 kW
Voltaggio	230 V, 400 V

## Standard equipment

In dotazione	Cesto per piatti, max 18 pezzi Ø 250
--------------	--------------------------------------

mm, Cesto universale con fondo  
piano per 18 piatti, Cestello per  
posate a 6 scomparti