Ristoattrezzature®

Smeg UD516D Easyline Series with 500x500 mm basket 6.7 kW Standard

Description

Professional front-loading dishwasher, double-walled, detergent dispenser, 500 mm basket, suitable for washing 600x400 mm GN1/1 trays

- Control panel: electronic
- No. of programmes: 6
- Hour baskets: 40/30/25/20/15
- Basket dimensions: 500x500 mm
- Useful load height: 415 mm
- Rinse aid dispenser: electronically controlled peristaltic pump
- Detergent dispenser: electronically controlled peristaltic pump
- Thermal-acoustic insulation: door and upper washing chamber area
- Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel
- Washing system: Washing pump with 'Soft Start' system
- Washing pump power: 0.7 kW
- Drain system: Drain pump for partial outflow of wash water, inspectable
- Filter system: Three-stage filtration integrated with the drain pump for separation of

residues and control of the water level in the tank
- Rinsing system: rinse pump and atmospheric boiler (HTR System)
- Tank heating element: 0.8 kW
- Boiler heating element: 4.50 kW / 3.00 kW single-phase
- TOTAL RINSING' function of the water in the tank after each wash
- EXTRA RINSE' function for prolonged rinsing
- Moulded basket guides
- Double-walled tank with rounded corners
- Boiler equipped with drain pipe for complete draining
- Insulated boiler
- Selectable 'Drain and clean tank' cycle
- Mains non-return device
- Thermostop for rinsing water temperature control
- Self-diagnosis system with fault indication
- Heating element 'Stand-by' function during periods of non-use

Dimensions

Dimensioni esterne	600x675x820 mm

Technical data

Alimentazione	Electric
Capacità acqua	11 Lt
Capacità boiler	6 Lt
Consumo d'acqua	3.2 kg
Frequenza	50 Hz
Materiale	aisi 304 stainless steel
Potenza Elettrica	6.7 kW
Voltaggio	230 V, 400 V

Standard equipment

In dotazione	Cesto per piatti, max 18 pezzi Ø 250 mm, Cesto universale con fondo piano, Cestello per posate a 6 scomparti, Cesto in filo per teglie GN1/1 prof. 60mm