

Cod: 96601754060006

## Smeg UD516DS Easyline Series with basket 500x500 mm 6.7 kW with softener



### Description

Professional dishwasher with front loading, double wall, detergent dispenser, softener, 500 mm basket, suitable for washing 600x400 mm GN1/1 trays Control panel: electronic No. of programmes: 6 Hourly baskets: 40/30/25/20/15 Basket dimensions: 500x500 mm Useful load height: 415 mm Rinse aid dispenser: electronically controlled peristaltic pump Detergent dispenser: electronically controlled peristaltic pump Thermal-acoustic insulation: door and upper washing chamber area Washing/rinsing impellers: 2 washing + 2 rinsing impellers in 304 stainless steel Washing system: Washing pump with 'Soft Start' system Washing pump power: 0.7 kW Drain system: Drain pump for partial outflow of wash water, inspectable Filter system: Three-stage filtration integrated with the drain pump for separation of residues and control of the water level in the tank Rinsing system: rinse pump and atmospheric boiler (HTR System) Tank heating element: 0.8 kW Boiler heating element: 4.50 kW / 3.00 kW single-phase TOTAL RINSING' function of the water in the tank after each wash EXTRA RINSE' function for prolonged rinsing Moulded basket guides Double-walled tank with rounded corners Boiler equipped with drain pipe for complete draining Insulated boiler Selectable 'Drain and clean tank' cycle Mains non-return device Thermostop for rinsing water temperature control Self-diagnosis system with fault

indication Heating element 'Stand-by' function during periods of non-use

## Dimensions

|                    |                |
|--------------------|----------------|
| Dimensioni esterne | 600x675x820 mm |
|--------------------|----------------|

## Technical data

|                   |                          |
|-------------------|--------------------------|
| Alimentazione     | Electric                 |
| Capacità acqua    | 11 Lt                    |
| Capacità boiler   | 6 Lt                     |
| Consumo d'acqua   | 3.2 kg                   |
| Frequenza         | 50 Hz                    |
| Materiale         | aisi 304 stainless steel |
| Potenza Elettrica | 6.7 kW                   |
| Voltaggio         | 230 V, 400 V             |

## Standard equipment

|              |   |
|--------------|---|
| In dotazione | Cesto per piatti, max 18 pezzi Ø 250 mm, Cesto universale con fondo piano, Cestello per posate a 6 scomparti, Cesto in filo per teglie GN1/1 prof. 60mm |
|--------------|---|