

Cod: 97771765078

## Smeg Osmotizer WO-20 150x550x490h mm 2 Lt



### Description

External reverse osmosis equipment, stainless steel, for models with HTR system

- Control panel: electronic
- Hourly output (1): 120 lt/h
- Expansion tank: 2 lt
- Recovery rate: 0.25
- Maximum output water conductivity (1): 5-30  $\mu\text{S}/\text{cm}$
- Inlet water pre-treatment: Activated carbon filter
- Inlet water pressure (min /max): 1.5 / 6 bar
- Inlet water hardness (max): 45° F
- Inlet water temperature (max): 35°C
- Inlet water conductivity (max): 1,200  $\mu\text{S}/\text{cm}$
- Notes (1): Output and conductivity depend on the chemical characteristics of the incoming water and the clogged state of the membranes
- Filter exhaustion alarm
- Water shortage alarm

- Anti-flooding alarm with automatic blockage
- Timed automatic membrane flushing in the event of prolonged inactivity
- Hour meter and litre counter

## Dimensions

Dimensioni esterne	150x550x490 mm
--------------------	----------------

## Technical data

Alimentazione	Electric
Capacità	2 Lt
Frequenza	50 Hz
Potenza Elettrica	0.69 kW
Pressione in ingresso acqua massima	6 bar
Pressione in ingresso acqua minima	1.5 bar
Produzione lt/h	120 Lt/h
Voltaggio	230 V