

Cod: 983600203632

Countertop refrigerated display case 88x56.8x68.6h cm straight glass 4-sided black glass 160 lt 0 +12 °C



Description

Indispensable on your counter, the **refrigerated counter display case** is an essential working tool. Useful for serving your preparations to customers at the right temperature at all times, it is easily placed on a worktop or counter and facilitates service.

You can store sweets and savoury food inside while maintaining the quality of the ingredients at any outside temperature.

Equipped with a double shelf, this model is black with straight glass panes.

Design and operation

Elegant and minimalist, the modern design of the **160 litre counter-top refrigerated display case** fits into any interior design context. Its square lines allow it to be easily placed in the room, where it offers a 360° view of the products it contains.

The **tempered glass** of which it is composed ensures an **excellent thermal seal** with **minimum energy dispersion**.

The structure is made of extra polished stainless steel capable of with standing the fast pace of the restaurant business. The steel resists abrasion and stains, is highly hygienic and easy to clean, and gives the equipment a professional touch.

Internally, the display case is equipped with a cold LED light to improve the visibility of products without increasing consumption and avoiding overheating of products.

Access to the refrigerated counter-top display case for catering is provided by **sliding openings at the back**, which allow for quick and practical use.

Inside you will find two **removable and adjustable**, **PVC-coated shelves**. One measures **800x320mm** and the other **800x350mm**. The **feet underneath** are also adjustable in height to suit your work requirements.

The showcase is electrically powered with a voltage of 230 V and a power of 0.16 kW. The operating temperature is adjustable between 0 +12 °C by means of a digital thermostat. The compressor is built-in and very low-noise.

The overall dimensions of the refrigerated counter display case are **880x568x686 mm** for a **gross weight of 70 kg**.

Cleaning and maintenance

The professional counter-top refrigerated display case is equipped with **automatic defrosting**, a mechanism that reduces cleaning and maintenance time.

The**automatic condensation evaporator** also allows you to control any condensation that may form inside, ensuring cleanliness and hygiene at all times.

For the overall cleaning of the machine, it is necessary to remove the included grilles and wash them with a degreasing solution.

For the tempered glass you can use water and vinegar to wipe with a soft cloth, taking care not to leave halos. Finally, a **mild soap and a soft cloth** will give the stainless steel parts a shine.

Sanitising should be carried out periodically while removing food residues should be done daily to ensure the highest possible efficiency.

Why it's the right product for you

Compact and linear design, compact dimensions and maximum display capacity make this display cabinet an essential piece of professional catering equipment.

Temperature control and glass panes on all 4 sides allow the refrigerated display case to offer complete customer service. The product is clearly visible and retains all its organoleptic properties.

Choose it also for its sustainability: the 160 litre refrigerated display case is a machine that ranks in **energy class B** with only **1038 kWh/year**, ensuring savings on energy bills and respect for the environment.

The **refrigerant gas** the display case uses is **R290**, a **100% natural** source that does not damage the ozone layer and, at the same time, offers excellent thermodynamic performance.

Finally, **refrigeration is of the ventilated type**: an evaporator placed outside the chamber distributes the cold evenly.

Dimensions

Dimensioni esterne	880x568x686 mm
Dimensioni imballo	935x620x720 mm

Technical data

Alimentazione	Electric
Capacità	160 Lt
Classe energetica	В
Frequenza	50 Hz
Gas refrigerante	R290
Peso	66 kg
Peso lordo	70 kg
Potenza Elettrica	0.16 kW
Temperatura d'esercizio	0 +12 °C
Voltaggio	230 V

Standard equipment

In dotazione	Luce interna a led e 2 griglie plastificate removibili e regolabili
	(800x320mm, 800x350mm)