

Cod: 102340020112222

Remote motorised refrigerated 2-door stainless steel refrigerated table -2 +8°C 122x60x86h cm



Description

The product features a stainless steel frame, provision for remote refrigeration unit (not included) with ventilated refrigeration, digital control unit, heated anti-condensation door stop frame, 60 mm insulation thickness, easily removable magnetic gaskets, cell with rounded corners, technical compartment lock with key, galvanised steel outer back and bottom panels and adjustable stainless steel feet.

Dimensions

| | |
|--------------------|-----------------|
| Dimensioni esterne | 1220x600x860 mm |
| Dimensioni imballo | 1250x630x910 mm |
| | |

| | |
|--------------------|----------------|
| Dimensioni interne | 902x430x589 mm |
|--------------------|----------------|

Technical data

| | |
|-----------------------------------|------------|
| Alimentazione | Electric |
| Capacità | 228 Lt |
| Gas unità refrigerante (optional) | r404 |
| Peso | 68 kg |
| Peso lordo | 74 kg |
| Potenza Elettrica | 0.5 kW |
| Refrigerazione | ventilated |
| Temperatura d'esercizio | -2 +8 °C |
| Voltaggio | 230 V |

Standard equipment

| | |
|--------------|---|
| In dotazione | 1 griglia plastificata 330x430 mm e 1 coppia di guide per porta |
|--------------|---|