

Cod: 102350020112224

Remote motorised refrigerated 2-door stainless steel refrigerated table with splashback -2 +8°C 122x60x96h cm



Description

The product features a stainless steel frame, 100 mm splashback, provision for remote refrigeration unit (not included) with ventilated refrigeration, digital control unit, heated anti-condensation door stop frame, 60 mm insulation thickness, easily removable magnetic gaskets, cell with rounded corners, technical compartment lock with key, galvanised steel outer back and bottom panels and adjustable stainless steel feet.

Dimensions

| | |
|--------------------|-----------------|
| Altezza alzatina | 100 mm |
| Dimensioni esterne | 1220x600x960 mm |

| | |
|--------------------|------------------|
| Dimensioni imballo | 1250x630x1010 mm |
| Dimensioni interne | 902x430x589 mm |

Technical data

| | |
|-----------------------------------|------------|
| Alimentazione | Electric |
| Capacità | 228 Lt |
| Frequenza | 50 Hz |
| Gas unità refrigerante (optional) | r404 |
| Peso | 61 kg |
| Peso lordo | 79 kg |
| Potenza Elettrica | 0.5 kW |
| Refrigerazione | ventilated |
| Temperatura d'esercizio | -2 +8 °C |
| Voltaggio | 230 V |

Standard equipment

| | |
|--------------|---|
| In dotazione | 1 griglia plastificata 330x430 mm e 1 coppia di guide per porta |
|--------------|---|