

Cod: 104270019317

Stainless steel seasoning cabinet for cold cuts 1 screen-printed glass door with black profiles capacity 625 I



## **Description**

The product has an outer structure in AISI 304 stainless steel with S.Brite finish, inner structure in AISI 304 stainless steel. Full glass door with screen-printed glass and black anodised profiles. - Interior with rounded corners and moulded bottom- 75 mm ecological polyurethane insulation-AISI 304 stainless steel racks, bars, grids and guides- Easily replaceable one-piece refrigeration unit- Temperature regulation range 0 / +30°C and humidity 40% ÷ 95%- Ventilated refrigeration with cataphoresis-treated evaporator- Class N air-cooled condensing unit (max +32°C)-Refrigerant gas R290- Automatic defrosting with electrical resistance- Resistance humidifier unit as standard (water connection required)- Condensate collection with removable tray- EVERtouch electronic control panel with 7" touch screen display- Internal lighting with K4000 LED bars- Key lock- Self-closing doors with 105° latch- Easily replaceable magnetic seals- Height-adjustable stainless steel feet (130-200 mm)- Wi-Fi connection module for remote management (automatically connects to the cloud via theWi-Fi network, allowing remote management of the operation andparameters of the cabinet or cell). Functional features: 10 preset recipes150 programmable recipes20 distinct phases for each recipe- Constant display of internal temperature and humidityremaining time of the current phase and icons with active function- USB port for

import/export of recipes, parameters, recorded data and possiblesoftware update- HACCP data log and alarms- Multi-language menu- Quick setting and display of temperature, humidity, ventilationventilation speed, air changes and run-stop- Display of temperature, humidity, weight and Ph graphs (optional)

## **Dimensions**

Dimensioni esterne	750x850x2080 mm
Dimensioni imballo	770x880x2235 mm

## **Technical data**

Alimentazione	Electric
Amperaggio	9.8 A
Capacità	625 Lt
Frequenza	50 Hz
Gas refrigerante	R290
Peso	149 kg
Peso lordo	171 kg
Potenza Elettrica	1.8 kW
Potenza frigorifera	0.498 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	0 +30 °C
Voltaggio	230 V

## Standard equipment

In dotazione	3 Coppie di guide inox, 9 barre in acciaio inox per ganci salumi e 36 ganci per salumi
--------------	--