

Cod: 1042700210318

## Stainless steel seasoning cabinet for cold cuts 2 glass doors with steel profiles capacity 1365 l



### Description

The product has an outer structure in AISI 304 stainless steel with S.Britee finish, inner structure in AISI 304 stainless steel. Glass doors with stainless steel profiles. General features: - Interior with rounded edges and moulded bottom- 75 mm insulation in ecological polyurethane- AISI 304 stainless steel racks, bars, grids and guides- Easily replaceable one-piece refrigeration unit- Temperature regulation range 0 / +30°C and humidity 40% ÷ 95%- Ventilated refrigeration with cataphoresis-treated evaporator- Class N air-cooled condensing unit (max +32°C)- Refrigerant gas R290- Automatic defrosting with electrical resistance- Resistance humidifier unit as standard (water connection required)- Condensate collection with removable tray- EVERtouch electronic control panel with 7" touch screen display- Internal lighting with K4000 LED bars- Key lock- Self-closing doors with 105° latch- Easily replaceable magnetic seals- Height-adjustable stainless steel feet (130-200 mm)- Wi-Fi connection module for remote management (automatically connects to the cloud via the Wi-Fi network, allowing remote management of the operation and parameters of the cabinet or cell). Functional features: 10 preset recipes 150 programmable recipes 20 distinct phases for each recipe- Constant display of internal temperature and humidity remaining time of the current phase and icons with active function- USB port for

import/export of recipes, parameters, recorded data and possible software update- HACCP data log and alarms- Multi-language menu- Quick setting and display of temperature, humidity, ventilation speed, air changes and run-stop- Display of temperature, humidity, weight and Ph graphs (optional)

## Dimensions

|                    |                  |
|--------------------|------------------|
| Dimensioni esterne | 1500x850x2080 mm |
| Dimensioni imballo | 1540x880x2235 mm |

## Technical data

|                         |            |
|-------------------------|------------|
| Alimentazione           | Electric   |
| Amperaggio              | 14 A       |
| Capacità                | 1365 Lt    |
| Frequenza               | 50 Hz      |
| Gas refrigerante        | R290       |
| Peso                    | 305 kg     |
| Peso lordo              | 330 kg     |
| Potenza Elettrica       | 2.6 kW     |
| Potenza frigorifera     | 1.04 kW    |
| Refrigerazione          | ventilated |
| Sbrinamento             | automatic  |
| Temperatura d'esercizio | 0 +30 °C   |
| Voltaggio               | 230 V      |

## Standard equipment

|              |   |
|--------------|---|
| In dotazione | 6 Coppie di guide inox, 18 barre in acciaio inox per ganci salumi e 72 ganci per salumi |
|--------------|---|