

Cod: 104280011317

## Meat and cheese maturing cabinet made of black plastic-coated steel 1 glass door capacity 625 l



### Description

The product has an external structure in black plastic-coated steel with a glass door, and an internal structure in mirror-polished AISI 304 stainless steel.

General features:

- Interior with rounded corners and moulded bottom
- 75 mm insulation in ecological polyurethane
- AISI 304 stainless steel racks, bars, grids and guides
- Easily replaceable one-piece refrigeration unit
- Temperature regulation range 0 / +30°C and humidity 40% ÷ 95%
- Ventilated refrigeration with cataphoresis-treated evaporator
- Class N air-cooled condensing unit (max +32°C)
- Refrigerant gas R290
- Automatic defrosting with electrical resistance
- Resistance humidifier unit as standard (water connection required)

- Condensate collection with removable tray
- EVERtouch electronic control panel with 7" touch screen display
- Internal lighting with K4000 LED bars
- Key lock
- Self-closing doors with 105° latch
- Easily replaceable magnetic seals
- Height-adjustable stainless steel feet (130-200 mm)
- Wi-Fi connection module for remote management (automatically connects to the cloud via the Wi-Fi network, allowing remote management of the operation and parameters of the cabinet or cell).

Functional features:

10 preset recipes

150 programmable recipes

20 distinct phases for each recipe

- Constant display of internal temperature and humidity

remaining time of the current phase and icons with active function

- USB port for import/export of recipes, parameters, recorded data and possible software update

- HACCP data log and alarms

- Multi-language menu

- Quick setting and display of temperature, humidity, ventilation

ventilation speed, air changes and run-stop

- Display of temperature, humidity, weight and Ph graphs (optional)

## Dimensions

Dimensioni esterne	750x850x2080 mm
Dimensioni imballo	770x880x2235 mm

## Technical data

Alimentazione	Electric
Amperaggio	9.8 A
Capacità	625 Lt
Frequenza	50 Hz
Gas refrigerante	R290
Peso	168 kg
Peso lordo	188 kg
Potenza Elettrica	1.8 kW
Potenza frigorifera	0.498 kW
Refrigerazione	ventilated

Sbrinamento	automatic
Temperatura d'esercizio	0 +30 °C
Voltaggio	230 V

### **Standard equipment**

In dotazione	5 coppie di guide inox e 5 griglie in acciaio inox
--------------	--