

Cod: 1042800210318

Stainless steel seasoning cabinet for meat and cheese 2 glass doors with steel profiles capacity 1365 l



Description

The product has an outer structure in AISI 304 stainless steel with S.Britee finish, inner structure in AISI 304 stainless steel. Glass doors with stainless steel profiles. General features: - Interior with rounded edges and moulded bottom- 75 mm insulation in ecological polyurethane- AISI 304 stainless steel racks, bars, grids and guides- Easily replaceable one-piece refrigeration unit- Temperature regulation range 0 / +30°C and humidity 40% ÷ 95%- Ventilated refrigeration with cataphoresis-treated evaporator- Class N air-cooled condensing unit (max +32°C)- Refrigerant gas R290- Automatic defrosting with electrical resistance- Resistance humidifier unit as standard (water connection required)- Condensate collection with removable tray- EVERtouch electronic control panel with 7" touch screen display- Internal lighting with K4000 LED bars- Key lock- Self-closing doors with 105° latch- Easily replaceable magnetic seals- Height-adjustable stainless steel feet (130-200 mm)- Wi-Fi connection module for remote management (automatically connects to the cloud via the Wi-Fi network, allowing remote management of the operation and parameters of the cabinet or cell). Functional features: 10 preset recipes 150 programmable recipes 20 distinct phases for each recipe- Constant display of internal temperature and humidity remaining time of the current phase and icons with active function- USB port for

import/export of recipes, parameters, recorded data and possible software update- HACCP data log and alarms- Multi-language menu- Quick setting and display of temperature, humidity, ventilation speed, air changes and run-stop- Display of temperature, humidity, weight and Ph graphs (optional)

Dimensions

Dimensioni esterne	1500x850x2080 mm
Dimensioni imballo	1540x880x2235 mm

Technical data

Alimentazione	Electric
Amperaggio	14 A
Capacità	1365 Lt
Frequenza	50 Hz
Gas refrigerante	R290
Peso	305 kg
Peso lordo	330 kg
Potenza Elettrica	2.6 kW
Potenza frigorifera	1.040 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	0 +30 °C
Voltaggio	230 V

Standard equipment

In dotazione	10 coppie guide inox e 10 griglie in acciaio inox
--------------	---