

Cod: 104280029318

Stainless steel seasoning cabinet for meat and cheese 2 screen-printed glass doors with black profiles capacity 1365 l



Description

The product has an outer structure in AISI 304 stainless steel with S.Brite finish, inner structure in AISI 304 stainless steel. Full glass doors with screen-printed glass and black anodised profiles.

- Interior with rounded corners and moulded bottom
- 75 mm ecological polyurethane insulation
- AISI 304 stainless steel racks, bars, grids and guides
- Easily replaceable one-piece refrigeration unit
- Temperature regulation range 0 / +30°C and humidity 40% ÷ 95%
- Ventilated refrigeration with cataphoresis-treated evaporator
- Class N air-cooled condensing unit (max +32°C)
- Refrigerant gas R290
- Automatic defrosting with electrical resistance
- Resistance humidifier unit as standard (water connection required)
- Condensate collection with removable tray
- EVERtouch electronic control panel with 7" touch screen display

- Internal lighting with K4000 LED bars
- Key lock
- Self-closing doors with 105° latch
- Easily replaceable magnetic seals
- Height-adjustable stainless steel feet (130-200 mm)
- Wi-Fi connection module for remote management (automatically connects to the cloud via the Wi-Fi network, allowing remote management of the operation and parameters of the cabinet or cell).

Functional features:

10 preset recipes

150 programmable recipes

20 distinct phases for each recipe

- Constant display of internal temperature and humidity remaining time of the current phase and icons with active function
- USB port for import/export of recipes, parameters, recorded data and possible software update
- HACCP data log and alarms
- Multi-language menu
- Quick setting and display of temperature, humidity, ventilation ventilation speed, air changes and run-stop
- Display of temperature, humidity, weight and Ph graphs (optional)

Dimensions

| | |
|--------------------|------------------|
| Dimensioni esterne | 1500x850x2080 mm |
| Dimensioni imballo | 1540x880x2235 mm |

Technical data

| | |
|---------------------|------------|
| Alimentazione | Electric |
| Amperaggio | 14 A |
| Capacità | 1365 Lt |
| Frequenza | 50 Hz |
| Gas refrigerante | R290 |
| Peso | 267 kg |
| Peso lordo | 292 kg |
| Potenza Elettrica | 2.6 kW |
| Potenza frigorifera | 1.040 kW |
| Refrigerazione | ventilated |
| Sbrinamento | automatic |

| | |
|-------------------------|----------|
| Temperatura d'esercizio | 0 +30 °C |
| Voltaggio | 230 V |

Standard equipment

| | |
|--------------|---|
| In dotazione | 10 coppie guide inox e 10 griglie in acciaio inox |
|--------------|---|