

Cod: 1042900110317

Stainless steel meat ripening cabinet 1 glass door with steel profiles capacity 625 l



Description

The product has an outer structure in AISI 304 stainless steel with S.Britee finish, inner structure in AISI 304 stainless steel. Glass door with stainless steel profiles. General features: - Interior with rounded corners and moulded bottom- 75 mm ecological polyurethane insulation- AISI 304 stainless steel racks, hook, grids and guides- Easily replaceable one-piece refrigeration unit- Temperature control range -2 / +10°C, Mod. Glass 0 / +10°C and humidity 40% ÷ 90%- Ventilated refrigeration with cataphoresis-treated evaporator- Class N air-cooled condensing unit (max +32°C)- Refrigerant gas R290- Automatic defrosting with electrical resistance- Automatic condensate evaporation with self-regulating electric heater- MEATouch electronic control panel with 4.3" touch screen display- Touch screen interface with gestures for even more intuitive control- LED UVC germicidal lamp as standard- Internal lighting with K4000 LED bars- Key lock- Self-closing doors with 105° latch- Easily replaceable magnetic seals- Height-adjustable stainless steel feet (130-200 mm)- Wi-Fi connection module for remote management Functional features: 3 preset recipes, programmable up to 4 stages separate for each recipe 10 fully customisable recipes that can be stored on the instrument- Controlled parameters for each phase; temperature, humidity fan speed, phase duration- Constant display of internal temperature and internal humidity-

HACCP data log and alarms- Alarm history combined with pop-up warning messages- Clock and date display (RTC)- Multi-language menu- Quick setting and display of temperature and humidity level- Manual or timed UVC germicidal lamp activation- Average display of temperature and humidity values humidity measured during the recipe- Wi-Fi connection for remote viewing and control- Possibility of software update via USB socket

Dimensions

| | |
|--------------------|-----------------|
| Dimensioni esterne | 750x850x2080 mm |
| Dimensioni imballo | 770x880x2235 mm |

Technical data

| | |
|-------------------------|------------|
| Alimentazione | Electric |
| Amperaggio | 5 A |
| Capacità | 625 Lt |
| Frequenza | 50 Hz |
| Gas refrigerante | R290 |
| Peso | 168 kg |
| Peso lordo | 188 kg |
| Potenza Elettrica | 1 kW |
| Potenza frigorifera | 0.498 kW |
| Refrigerazione | ventilated |
| Sbrinamento | automatic |
| Temperatura d'esercizio | 0 +10 °C |
| Voltaggio | 230 V |

Standard equipment

| | |
|--------------|---|
| In dotazione | 3 Coppie guide inox, 3 griglie in acciaio inox GN 2/1 530x650 mm, 1 ganciera per carne, 2 ganci per carne |
|--------------|---|