

Cod: 104290011317

## Meat ripening cabinet made of black plastic-coated steel 1 glass door capacity 625 l



### Description

The product has an external structure in black plastic-coated steel with a glass door, and an internal structure in mirror-polished AISI 304 stainless steel. General features: - Interior with rounded corners and moulded bottom- 75 mm ecological polyurethane insulation- AISI 304 stainless steel racks, hooks, grids and guides- Easily replaceable one-piece refrigeration unit- Temperature control range -2 / +10°C, Mod. Glass 0 / +10°C and humidity 40% ÷ 90%- Ventilated refrigeration with cataphoresis-treated evaporator- Class N air-cooled condensing unit (max +32°C)- Refrigerant gas R290- Automatic defrosting with electrical resistance- Automatic condensate evaporation with self-regulating electric heater- MEATouch electronic control panel with 4.3" touch screen display- Touch screen interface with gestures for even more intuitive control- LED UVC germicidal lamp as standard- Internal lighting with K4000 LED bars- Key lock- Self-closing doors with 105° latch- Easily replaceable magnetic seals- Height-adjustable stainless steel feet (130-200 mm)- Wi-Fi connection module for remote management Functional features: 3 preset recipes, programmable up to 4 stages separate for each recipe 10 fully customisable recipes that can be stored on the instrument- Controlled parameters for each phase; temperature, humidity fan speed, phase duration- Constant display of internal temperature and internal humidity-

HACCP data log and alarms- Alarm history combined with pop-up warning messages- Clock and date display (RTC)- Multi-language menu- Quick setting and display of temperature and humidity level- Manual or timed UVC germicidal lamp activation- Average display of temperature and humidity values humidity measured during the recipe- Wi-Fi connection for remote viewing and control- Possibility of software update via USB socket

## Dimensions

Dimensioni esterne	750x850x2080 mm
Dimensioni imballo	770x880x2235 mm

## Technical data

Alimentazione	Electric
Amperaggio	5 A
Capacità	625 Lt
Frequenza	50 Hz
Gas refrigerante	R290
Peso	168 kg
Peso lordo	188 kg
Potenza Elettrica	1 kW
Potenza frigorifera	0.498 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	0 +10 °C
Voltaggio	230 V

## Standard equipment

In dotazione	3 Coppie guide inox, 3 griglie in acciaio inox GN 2/1 530x650 mm, 1 ganciera per carne, 2 ganci per carne
--------------	---