

Cod: 104290012317

## Stainless steel meat ripening cabinet 1 solid door capacity 625 l



### Description

The product has an outer structure in AISI 304 stainless steel with S.Brite finish, and an inner structure in AISI 304 stainless steel with solid door.

General features:

- Interior with rounded edges and moulded bottom
- 75 mm insulation in ecological polyurethane
- AISI 304 stainless steel racks, hook, grids and guides
- Easily replaceable one-piece refrigeration unit
- Temperature control range -2 / +10°C, Mod. Glass 0 / +10°C and humidity 40% ÷ 90%
- Ventilated refrigeration with cataphoresis-treated evaporator
- Class N air-cooled condensing unit (max +32°C)
- REM models (without condensing unit) fitted with thermostatic valve
- Refrigerant gas R290
- Automatic defrosting with electrical resistance
- Automatic condensate evaporation with self-regulating electric heater

- MEATouch electronic control panel with 4.3" touch screen display
- Touch screen interface with gestures for even more intuitive control
- LED UVC germicidal lamp as standard
- Internal lighting with K4000 LED bars
- Key lock
- Self-closing doors with 105° latch
- Easily replaceable magnetic seals
- Height-adjustable stainless steel feet (130-200 mm)
- Wi-Fi connection module for remote management

Functional features:

3 preset recipes, programmable up to 4 stages  
separate for each recipe

10 fully customisable recipes that can be stored  
on the instrument

- Controlled parameters for each phase; temperature, humidity  
fan speed, phase duration

- Constant display of internal temperature and  
internal humidity

- HACCP data log and alarms

- Alarm history combined with pop-up warning messages

- Clock and date display (RTC)

- Multi-language menu

- Quick setting and display of temperature and  
humidity level

- Manual or timed UVC germicidal lamp activation

- Average display of temperature and humidity values  
humidity measured during the recipe

- Wi-Fi connection for remote viewing and control

- Possibility of software update via USB socket

## Dimensions

Dimensioni esterne	750x850x2080 mm
Dimensioni imballo	770x880x2235 mm

## Technical data

Alimentazione	Electric
Amperaggio	5 A
Capacità	625 Lt
Frequenza	50 Hz
Gas refrigerante	R290
Peso	133 kg

Peso lordo	155 kg
Potenza Elettrica	1.0 kW
Potenza frigorifera	0.498 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	-2 +10 °C
Voltaggio	230 V

### Standard equipment

In dotazione	3 Coppie guide inox, 3 griglie in acciaio inox GN 2/1 530x650 mm, 1 ganciera per carne, 2 ganci per carne
--------------	---