

Cod: 104290029318

Stainless steel meat maturation cabinet 2 doors in screen-printed glass with black profiles capacity 1365 l



Description

The product has an outer structure in AISI 304 stainless steel with S.Brite finish, inner structure in AISI 304 stainless steel. Full glass doors with screen-printed glass and black anodised profiles. General features: - Interior with rounded corners and moulded bottom- 75 mm ecological polyurethane insulation- AISI 304 stainless steel racks, hooks, grids and guides- Easily replaceable one-piece refrigeration unit- Temperature control range -2 / +10°C, Mod. Glass 0 / +10°C and humidity 40% ÷ 90%- Ventilated refrigeration with cataphoresis-treated evaporator- Class N air-cooled condensing unit (max +32°C)- REM models (without condensing unit) fitted with thermostatic valve- Refrigerant gas R290- Automatic defrosting with electrical resistance- Automatic condensate evaporation with self-regulating electric heater- MEATouch electronic control panel with 4.3" touch screen display- Touch screen interface with gestures for even more intuitive control- LED UVC germicidal lamp as standard- Internal lighting with K4000 LED bars- Key lock- Self-closing doors with 105° latch- Easily replaceable magnetic seals- Height-adjustable stainless steel feet (130-200 mm)- Wi-Fi connection module for remote management Functional features: 3 preset recipes, programmable up to 4 stages separate for each recipe 10 fully customisable recipes that can be stored on the instrument- Controlled parameters for each

phase; temperature, humidityfan speed, phase duration- Constant display of internal temperature andinternal humidity- HACCP data log and alarms- Alarm history combined with pop-up warning messages- Clock and date display (RTC)- Multi-language menu- Quick setting and display of temperature andhumidity level- Manual or timed UVC germicidal lamp activation- Average display of temperature and humidity valueshumidity measured during the recipe- Wi-Fi connection for remote viewing and control- Possibility of software update via USB socket

Dimensions

Dimensioni esterne	1500x850x2080 mm
Dimensioni imballo	1540x880x2235 mm

Technical data

Alimentazione	Electric
Amperaggio	7.5 A
Capacità	1365 Lt
Frequenza	50 Hz
Gas refrigerante	R290
Peso	267 kg
Peso lordo	292 kg
Potenza Elettrica	1.7 kW
Potenza frigorifera	1.04 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	0 +10 °C
Voltaggio	230 V

Standard equipment

In dotazione	6 Coppie guide inox, 6 griglie in acciaio inox GN 2/1 530x650 mm, 1 ganciera per carne, 4 ganci per carne
--------------	---