

Cod: 104420032406

# Display saladette refrigerator counter with straight glass and intermediate shelf 3 doors 136.5x70x85h cm



#### **Description**

Spacious and ideal for delicatessens and canteens, the **display saladette refrigerated counter** is professional catering equipment designed to **store and display** food.

It consists of two parts: one in stainless steel with **3 refrigerated doors** and one in glass for display purposes. **The display case is upright with a shelf**.

Designed to be placed in the dining room, the professional refrigerated counter is intended to keep ready preparations fresh and provide a complete and detailed view to customers.

## Design and operation

The design of our display saladette refrigeration counter is clean and straightforward to ensure easy cleaning and convenient installation. The **stainless steel structure** ensures robustness and heat retention due to its thickness and features **3 doors with ergonomic handles**. The doors

close automatically and the presence of gaskets limits energy loss while ensuring a stable temperature.

The **open top** is designed to accommodate standard GN deli trays. The machine can accommodate:

• 4 GN 1/1 trays

or

1 gn 1/1 tray + 2 gn 1/2 trays + 3 gn 1/3 trays + 2 gn 1/2 trays

The traysare not included and can be purchased in the optional section.

In the upper part we find the display area made entirely of **straight tempered glass** that allows a panoramic view of the product while ensuring a good thermal seal. The display case includes **a** fixed, non-adjustable **intermediate shelf**.

In terms of overall dimensions, Ristoattrezzature's display saladette refrigerator counter measures 1365x700x850h mm for a capacity of 368 litres.

Convenient dimensions that also meet the needs of medium-large businesses. In the machine, the **motor is incorporated** and **refrigeration is static**. Cold is generated through a plate inside the chamber and progressively propagated by radiation.

The fan in the refrigerated display case **ensures the same temperature for all preparations**. Its action **equalises the temperature in the chamber**.

The operating temperature is adjustable via a digital thermostat and can be set between + 2° C and + 8° C. The gradation can be monitored on a display on the bottom, where the power button is also located.

The saladette cooler is electrically powered with a power of 0.28 kW and a voltage of 230 V.

## Cleaning and maintenance

In order to keep our display saladette refrigerator counter performing at all times, it is necessary to carry out **regular and careful cleaning**.

First of all, **unplug the power socket** and clean all container compartments and trays with **a soft cloth and mild detergent**. Chlorinated abrasive detergents or acids would irreparably damage the protective film of the stainless steel. Also carefully clean the door gaskets with **warm soapy water**, taking care to dry them thoroughly. Each separately purchased tray has rounded corners for easy cleaning.

For the maintenance of stainless steel, remember **never to leave dirt stains on steel parts** or water or other liquids for **too long**. When sanitising it, **never use abrasive scouring pads** or other tools that could scratch it.

## Why it is the right product for you

**Spacious, practical and comfortable** to use, the display saladette refrigerator counter is a **high-performance** and **capacious machine**. The large glass windows offer excellent visibility to the preparations, keeping them always at the right temperature. Not only that, the internal

organisation it offers ensures hygiene and order both through the various trays and by taking advantage of the additional shelf.

Excellent value for money and low consumption. Finally, the refrigerant gas used, **R290**, ensures excellent thermodynamic performance and **respect for the environment**. The source is completely natural and does not damage the ozone layer.

Buy the display saladette refrigerator counter for your premises, ideal to be placed in the hall and perfect for delicatessens, sandwich shops and fast food outlets.

#### **Dimensions**

Dimensioni esterne	1365x700x850 mm
--------------------	-----------------

#### **Technical data**

Alimentazione	Electric
Capacità	368 Lt
Frequenza	50 Hz
Gas refrigerante	R290
Potenza Elettrica	0.28 kW
Refrigerazione	static
Temperatura d'esercizio	+2 +8 °C
Voltaggio	230 V