

Cod: 104430011063

Stainless steel refrigerated cabinet 1 glass door 700 litres ventilated +2 +10°C



Description

The product features an AISI 304 stainless steel construction with glass door. General features: - 2/1 Gastronorm cabinets with a depth of 815 mm- interior with rounded corners and moulded bottom- 75 mm ecological polyurethane insulation- racks (52 mm pitch) and AISI 304 stainless steel guides- ventilated refrigeration with evaporator treated with anti-corrosion paint- easily replaceable monobloc refrigerating unit- glass door models with class N condensing unit (max +32°C)- refrigerant gas R290 (propane)- electronic Energy Saving control panel with HACCP function- temperature and dirty condenser alarm management- rapid cooling "Overcooling" function- possibility of high and low humidity setting- automatic hot gas defrosting- serial port for connection to supervisory systems- automatic condensate evaporation with hot gas tube- internal lighting- key lock- self-closing doors with 105° stop- easily replaceable magnetic seals- height-adjustable stainless steel feet (130-200 mm) N.B. :To take advantage of the Industry 4.0 tax credit select the WIFI option.

Dimensions

Dimensioni esterne	750x815x2080 mm
Dimensioni imballo	770x880x2235 mm

Technical data

Alimentazione	Electric
Amperaggio	1.55 A
Capacità	700 Lt
Capacità netta	625 Lt
Frequenza	50 Hz
Gas refrigerante	R290
Peso	156 kg
Peso lordo	168 kg
Potenza Elettrica	0.24 kW
Potenza frigorifera	0.406 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	+2 +10 °C
Voltaggio	230 V

Standard equipment

In dotazione	3 griglie plastificate GN2/1 con guide INOX per ciascuna porta
--------------	--