

Cod: 104430031319

Stainless steel refrigerated cabinet 3 glass doors 2300 litres ventilated +2 +10°C



Description

The product features an all-AISI 304 stainless steel construction with glass doors.

General features:

- 2/1 Gastronorm cabinets with a depth of 815 mm
- interior with rounded corners and moulded bottom
- 75 mm ecological polyurethane insulation
- racks (52 mm pitch) and AISI 304 stainless steel guides
- ventilated refrigeration with evaporator treated with anti-corrosion paint
- easily replaceable monobloc refrigerating unit
- double refrigerating unit
- glass door models with class N condensing unit (max +32°C)
- refrigerant gas R290 (propane)
- electronic Energy Saving control panel with HACCP function
- temperature and dirty condenser alarm management

- rapid cooling "Overcooling" function
- possibility of high and low humidity setting
- automatic hot gas defrosting
- serial port for connection to supervisory systems
- automatic condensate evaporation with hot gas tube
- internal lighting
- key lock
- self-closing doors with 105° stop
- easily replaceable magnetic seals
- height-adjustable stainless steel feet (130-200 mm)

N.B. :To take advantage of the Industry 4.0 tax credit select the WIFI option.

Dimensions

Dimensioni esterne	2250x815x2080 mm
Dimensioni imballo	2290x880x2235 mm

Technical data

Alimentazione	Electric
Amperaggio	4.86 A
Capacità	2102 Lt
Capacità netta	2300 Lt
Frequenza	50 Hz
Gas refrigerante	R290
Peso	369 kg
Peso lordo	401 kg
Potenza Elettrica	0.78 kW
Potenza frigorifera	1.426 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	+2 +10 °C
Voltaggio	230 V

Standard equipment

In dotazione	3 griglie plastificate GN2/1 con guide
--------------	--

INOX per ciascuna porta