

Cod: 104430032319

Stainless steel refrigerated cabinet 3 blind doors 2300 lt ventilated -2 +10°C



Description

The product features an all-AISI 304 stainless steel construction with blind doors. General features: - 2/1 Gastronorm cabinets with a depth of 815 mm- interior with rounded corners and moulded bottom- 75 mm ecological polyurethane insulation- racks (52 mm pitch) and AISI 304 stainless steel guides- ventilated refrigeration with evaporator treated with anti-corrosion paint- easily replaceable monobloc refrigerating unit- with double refrigerating unit- solid door models with SN-T class condensing unit (max +43°C)- refrigerant gas R290 (propane)- electronic Energy Saving control panel with HACCP function- temperature and dirty condenser alarm management- rapid cooling "Overcooling" function- possibility of high and low humidity setting- automatic hot gas defrosting- serial port for connection to supervisory systems- automatic condensate evaporation with hot gas tube- internal lighting- key lock- self-closing doors with 105° stop- easily replaceable magnetic seals- height-adjustable stainless steel feet (130-200 mm) N.B. :To take advantage of the Industry 4.0 tax credit select the WIFI option.

Dimensions

Dimensioni esterne	2250x815x2080 mm
Dimensioni imballo	2290x880x2235 mm

Technical data

Alimentazione	Electric
Amperaggio	4.56 A
Capacità	2300 Lt
Capacità netta	2102 Lt
Classe energetica	D
Frequenza	50 Hz
Gas refrigerante	R290
Peso	315 kg
Peso lordo	347 kg
Potenza Elettrica	0.74 kW
Potenza frigorifera	1.426 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	-2 +10 °C
Voltaggio	230 V

Standard equipment

In dotazione	3 griglie plastificate GN2/1 con guide INOX per ciascuna porta
--------------	--