

Cod: 104440012063

Stainless steel refrigerated freezer cabinet 1 solid door 700 l ventilated -10 -22°C



Description

The product features an all-AISI 304 stainless steel construction with a solid door.

General features:

- 2/1 Gastronorm cabinets with a depth of 815 mm
- interior with rounded corners and moulded bottom
- 75 mm ecological polyurethane insulation
- racks (52 mm pitch) and AISI 304 stainless steel guides
- ventilated refrigeration with evaporator treated with anti-corrosion paint
- easily replaceable monobloc refrigerating unit
- solid door models with SN-T class condensing unit (max +43°C)
- refrigerant gas R290 (propane)
- electronic Energy Saving control panel with HACCP function
- temperature and dirty condenser alarm management
- rapid cooling "Overcooling" function

- possibility of high and low humidity setting
- automatic hot gas defrosting
- serial port for connection to supervisory systems
- automatic condensate evaporation with hot gas tube
- internal lighting
- key lock
- self-closing doors with 105° stop
- easily replaceable magnetic seals
- height-adjustable stainless steel feet (130-200 mm)

N.B. :To take advantage of the Industry 4.0 tax credit select the WIFI option.

Dimensions

| | |
|--------------------|-----------------|
| Dimensioni esterne | 750x815x2080 mm |
| Dimensioni imballo | 770x880x2235 mm |

Technical data

| | |
|-------------------------|------------|
| Alimentazione | Electric |
| Amperaggio | 3.53 A |
| Capacità | 700 Lt |
| Capacità netta | 625 Lt |
| Classe energetica | C |
| Frequenza | 50 Hz |
| Gas refrigerante | R290 |
| Peso | 140 kg |
| Peso lordo | 152 kg |
| Potenza Elettrica | 0.57 kW |
| Potenza frigorifera | 0.593 kW |
| Refrigerazione | ventilated |
| Sbrinamento | automatic |
| Temperatura d'esercizio | -10 -22 °C |
| Voltaggio | 230 V |

Standard equipment

| | |
|--|--|
| | |
|--|--|

In dotazione

3 griglie plastificate GN2/1 con guide
INOX per ciascuna porta