

Cod: 1045100209974

Stainless steel refrigerated double temperature cabinet 2 separate doors 1400 l -2 +10°C / -2 +10°C



Description

The product features a full AISI 304 stainless steel construction with blind doors, two separate interiors with a net capacity of 625 litres each. Both the left and right side have an operating temperature of -2 +10°C.

General features:

- Gastronorm 2/1 cabinets with a depth of 815 mm
- interior with rounded corners and moulded bottom
- 75 mm ecological polyurethane insulation
- racks (52 mm pitch) and guides in AISI 304 stainless steel
- ventilated refrigeration with evaporator treated with anti-corrosion paint
- easily replaceable monobloc refrigerating unit
- solid door models with SN-T class condensing unit (max +43°C)
- refrigerant gas R290 (propane)
- electronic Energy Saving control panel with HACCP function

- temperature and dirty condenser alarm management
- rapid cooling "Overcooling" function
- possibility of high and low humidity setting
- automatic hot gas defrosting
- serial port for connection to supervisory systems
- automatic condensate evaporation with hot gas tube
- internal lighting
- key lock
- self-closing doors with 105° stop
- easily replaceable magnetic seals
- height-adjustable stainless steel feet (130-200 mm)

N.B. :To take advantage of the Industry 4.0 tax credit select the WIFI option.

Dimensions

Dimensioni esterne	1500x815x2080 mm
Dimensioni imballo	1540x880x2235 mm

Technical data

Alimentazione	Electric
Amperaggio	2.9 A
Capacità	1400 Lt
Capacità netta	1250 Lt
Classe energetica	C
Frequenza	50 Hz
Gas refrigerante	R290
Peso	232 kg
Peso lordo	255 kg
Potenza Elettrica	0.23 kW
Potenza frigorifera	0.812 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	-2 +10 °C
Voltaggio	230 V

Standard equipment

In dotazione

3 griglie plastificate GN2/1 con guide
INOX per ciascuna porta