

Cod: 1045200106374

Refrigerated double-temperature cabinet depth 85 cm stainless steel 1 door with 2 separate doors 700 l -2 +10°C / -2 +10°C



Description

The product features a construction entirely in AISI 304 stainless steel with blind doors, two separate interiors both with a capacity of 300 lt. Both the upper and lower sections have an operating temperature of -2 +10°C.

General features:

- Gastronorm 2/1 cabinets with 850 mm depth
- interior with rounded edges and moulded bottom
- 75 mm ecological polyurethane insulation
- racks (52 mm pitch) and guides in AISI 304 stainless steel
- ventilated refrigeration with evaporator treated with anti-corrosion paint
- easily replaceable buffer refrigeration unit
- solid door models with SN-T class condensing unit (max +43°C)
- refrigerant gas R290 (propane)
- electronic Energy Saving control panel with HACCP function

- temperature and dirty condenser alarm management
- rapid cooling "Overcooling" function
- possibility of high and low humidity setting
- automatic defrosting with resistor
- serial port for connection to supervisory systems
- automatic evaporation of condensate with self-regulating resistor
- internal lighting
- locking with keys
- self-closing doors with 105° stop
- easily replaceable magnetic seals
- height-adjustable stainless steel feet (130-200 mm)

N.B. :To take advantage of the Industry 4.0 tax credit select the WIFI option.

Dimensions

Dimensioni esterne	750x850x2080 mm
Dimensioni imballo	770x880x2235 mm

Technical data

Alimentazione	Electric
Amperaggio	3 A
Capacità	700 Lt
Capacità netta	600 Lt
Classe energetica	B
Frequenza	50 Hz
Gas refrigerante	R290
Peso	162 kg
Peso lordo	174 kg
Potenza Elettrica	0.62 kW
Potenza frigorifera	0.64 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	-2 +10 °C
Voltaggio	230 V

Standard equipment

In dotazione

2 griglie plastificate GN2/1 con guide
INOX per ciascuna porta