

Cod: 1045200106374

**Refrigerated double-temperature cabinet depth 85 cm stainless steel 1 door with 2 separate doors 700 l -2 +10°C / -2 +10°C**



## Description

The product features a construction entirely in AISI 304 stainless steel with blind doors, two separate interiors both with a capacity of 300 lt. Both the upper and lower sections have an operating temperature of -2 +10°C. General features: - Gastronorm 2/1 cabinets with 850 mm depth- interior with rounded edges and moulded bottom- 75 mm ecological polyurethane insulation- racks (52 mm pitch) and guides in AISI 304 stainless steel- ventilated refrigeration with evaporator treated with anti-corrosion paint- easily replaceable buffer refrigeration unit- solid door models with SN-T class condensing unit (max +43°C)- refrigerant gas R290 (propane)- electronic Energy Saving control panel with HACCP function- temperature and dirty condenser alarm management- rapid cooling "Overcooling" function- possibility of high and low humidity setting- automatic defrosting with resistor- serial port for connection to supervisory systems- automatic evaporation of condensate with self-regulating resistor- internal lighting- locking with keys- self-closing doors with 105° stop- easily replaceable magnetic seals- height-adjustable stainless steel feet (130-200 mm) N.B. :To take advantage of the Industry 4.0 tax credit select the WIFI option.

## Dimensions

Dimensioni esterne	750x850x2080 mm
Dimensioni imballo	770x880x2235 mm

## Technical data

Alimentazione	Electric
Amperaggio	3 A
Capacità	700 Lt
Capacità netta	600 Lt
Classe energetica	B
Frequenza	50 Hz
Gas refrigerante	R290
Peso	162 kg
Peso lordo	174 kg
Potenza Elettrica	0.62 kW
Potenza frigorifera	0.64 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	-2 +10 °C
Voltaggio	230 V

## Standard equipment

In dotazione	2 griglie plastificate GN2/1 con guide INOX per ciascuna porta
--------------	--