

Cod: 1045200209974

Refrigerated double temperature cabinet depth 85 cm stainless steel 2 separate doors 1400 lt -2 +10°C / -2 +10°C



Description

The product features an entirely AISI 304 stainless steel construction with blind doors, two separate 625 litre interiors. Both the left and right sides have an operating temperature of -2 +10°C. General features: - 2/1 Gastronorm cabinets 850 mm deep- interior with rounded corners and moulded bottom- 75 mm ecological polyurethane insulation- racks (52 mm pitch) and guides in AISI 304 stainless steel- ventilated refrigeration with evaporator treated with anti-corrosion paint- easily replaceable buffer refrigeration unit- solid door models with SN-T class condensing unit (max +43°C)- refrigerant gas R290 (propane)- electronic Energy Saving control panel with HACCP function- temperature and dirty condenser alarm management- rapid cooling "Overcooling" function- possibility of high and low humidity setting- automatic defrosting with resistor- serial port for connection to supervisory systems- automatic evaporation of condensate with self-regulating resistor- internal lighting- locking with keys- self-closing doors with 105° stop- easily replaceable magnetic seals- height-adjustable stainless steel feet (130-200 mm) N.B. :To take advantage of the Industry 4.0 tax credit select the WIFI option.

Dimensions

Dimensioni esterne	1500x850x2080 mm
Dimensioni imballo	1540x880x2235 mm

Technical data

Alimentazione	Electric
Amperaggio	2.9 A
Capacità	1400 Lt
Capacità netta	1250 Lt
Classe energetica	C
Frequenza	50 Hz
Gas refrigerante	R290
Peso	232 kg
Peso lordo	255 kg
Potenza Elettrica	0.46 kW
Potenza frigorifera	0.812 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura d'esercizio	-2 +10 °C
Voltaggio	230 V

Standard equipment

In dotazione	3 griglie plastificate GN2/1 con guide INOX per ciascuna porta
--------------	--