

Cod: 11106026014149

**Automatic charcuterie slicer professional belt system fixed sharpener
chromium-plated blade Ø 300 mm 0.23 kW**



Description

Professional automatic slicing machine designed for cutting cold meats, cheese, bread and fish. The automatic feed mechanism is operated by a lever under the flat support, which allows the operator to decide whether to operate the slicer also manually.

The line, which has been carefully designed down to the smallest detail with large radii and no sharp edges, allows easy and complete cleaning, also guaranteed by the BLC system, the sliding carriage block, which allows the product plate and its support to be removed, thus providing convenient access even to the part below the plate itself; in this case, a special safety mechanism allows disassembly only when the slice adjustment bulkhead is in the "0" position so that the blade is completely protected. Equipped with a digital panel for the selection of the 3 speeds and 3 strokes including the slice counter function. The S.C.A. plate suitable for cutting irregularly shaped, unevenly shaped pieces of cold cuts and/or meat is also standard on this model.

Designed in accordance with current safety standards, this slicer has the following features:

- Robust stainless steel lower structure for greater stability.
- Cast aluminium base with polished anodic oxidation.
- Professional, hardened, ground and hard-chrome plated blade.
- Presser in cast aluminium protected with oxidation.
- Professional, quiet, powerful and robust self-ventilated asynchronous induction motor
- Anodic oxidation-protected cast aluminium canvas.
- Graduated knob for cutting thickness adjustment up to 15 mm
- Blade shaft mounted on double ball bearing.
- Fixed blade protection ring.

Dimensions

Capacità di taglio	290x200 mm
Corsa carrello	325 mm
Diametro lama	300 mm
Dimensioni esterne	685x540x545 mm
Dimensioni imballo	630x520x620 mm
Dimensioni piano d'appoggio	487x355 mm
Spessore massimo di taglio	15 mm

Technical data

Alimentazione	Electric
Frequenza	50 Hz
Peso	49 kg
Potenza Elettrica	0.23 kW
Voltaggio	230 V