

Cod: 11215000042016

4-burner gas cooker with pilot flame and ventilated electric oven 80x70x85h cm



Description

4-burner gas cooker with ventilated electric oven, stainless steel construction. Moulded, double-walled oven door and sturdy handle. Thermosetting plastic knobs. Heating by means of watertight burners with stabilised flame and superimposed crown with different power ratings (6.2 kw and 8.5 kw). Each burner is equipped with a safety gas cock that allows the power to be adjusted from maximum to minimum. Safety guaranteed by a thermocouple kept active by the pilot burner flame. Floor grates and burners made of RAAF matt enamelled cast iron resistant to alkalis, acids and fire. Floor grates positioned on a moulded basin with rounded edges to ensure easy cleaning and protect against overflowing liquids. Moulded basins with rounded stainless steel edges located under the burners and easily removable for cleaning. Ventilated 1/1 GN electric oven. Removable stainless steel oven rack. Thick steel oven floor reinforced with a series of ribs. Insulation of baking chamber and oven door ensured by a layer of ceramic fibre resistant to high temperatures. Oven heating by means of special high-temperature-resistant steel heating elements placed under the sole and in the baking chamber ceiling. Air movement guaranteed by a stainless steel fan driven by a powerful electric motor. Possibility of selecting various types of heating, both static and ventilated, both diffusive heating from below and grill, and global heating.

Equipped with a thermostat that allows you to adjust the temperature between 90°C and 300°C. Manually reset safety thermostat against overheating. Laser-cut top finish to ensure a "head-to-head" combination of tops and binding of tops to each other. Height-adjustable stainless steel feet. Tested with methane or LPG gas according to user requirements.

Dimensions

Dimensioni esterne	800x700x850 mm
--------------------	----------------

Technical data

Alimentazione	Electric, Gas
Peso	125 kg
Potenza Bruciatori	6.2 (x2) kW, 8.5 (x2) kW
Potenza Forno	3.65 kW
Potenza Gas	29.4 kW
Temperatura d'esercizio	+90 +300 °C
Voltaggio	400 V