

Cod: 112190021722016

2-burner gas cooker with pilot flame cast iron cooking plate and gas oven 28.2 kW 80x70x85h cm



Description

2-burner gas cooker with cast-iron plate and gas oven, stainless steel construction. Moulded, double-walled oven door and sturdy handle. Thermosetting plastic knobs. Thick cast-iron cooking surface with rounded corners, made of a single casting. Removable central round insert. Circular central burner made of stainless steel, suitable for operation at high temperatures. Maximum temperature of about 500°C at the hottest central point and then degrading towards the edges through differentiated isothermal zones. Heating by means of watertight burners with a stabilised overlapping flame with different power ratings (6.2 kW and 8.5 kW). Each burner is equipped with a safety gas cock that allows the power to be adjusted from maximum to minimum. Safety guaranteed by a thermocouple kept active by the pilot burner flame. Floor grates and burners made of RAAF matt enamelled cast iron resistant to alkalis, acids and fire. Floor grates positioned on a moulded basin with rounded edges to ensure easy cleaning and protect against overflowing liquids. Moulded basins with rounded stainless steel edges located under the burners and easily removable for cleaning. 2/1 GN gas oven. Removable stainless steel oven grate. Thick steel oven floor reinforced with a series of ribs. Insulation of baking chamber and oven door ensured by a layer of ceramic fibre resistant to high temperatures. Rapid temperature rise and heat retention by

means of a high-performance stabilised flame burner with integrated diffuser, suitable for working at high temperatures. The oven burner is equipped with a thermostatic safety gas valve that allows the temperature to be regulated up to 300°C. Safety ensured by a thermocouple kept active by the burner flame. Laser-cut top finish to ensure a "head-to-toe" combination of tops and binding of tops to each other. Height-adjustable stainless steel feet. Tested with methane or LPG gas according to user requirements.

Dimensions

Dimensioni esterne	800x700x850 mm
--------------------	----------------

Technical data

Alimentazione	Gas
Peso	130 kg
Potenza Bruciatori	6 (x1) kW, 6.2 (x1) kW, 8.5 (x1) kW
Potenza Gas	28.2 kW