

Cod: 112630010242858

**Refrigerated pastry counter straight glazing ventilated with intermediate shelf red +2 +6 °C 222,7x94x122,4h cm**



## Description

Strengths:

- Technology, design and production 'Made in Italy';
- Compact dimensions (depth of only 945 mm);
- Ideal for any type of environment;
- Low energy consumption and low environmental impact;
- Stainless steel work and display surface;
- Easily removable stainless steel display trays to guarantee easy cleaning of the display case;
- Easily removable and customisable front and side finishes;
- Hot air glass anti-fogging system;
- White pre-painted sheet metal tub (suitable for food contact with high-pressure injected polyurethane insulation without environmentally hazardous CFC gas for the environment (density 40 Kg / m<sup>3</sup>);
- Can be ducted;

- Easy and immediate installation.
- Sheet metal side panels with tempered glass sides;
- Electronic control panel;
- Ceiling lamp with LED lighting;
- 2 open compartments, complete with intermediate shelf;
- 1 intermediate shelf in tempered glass;
- Condensate evaporator tray equipped with PTC resistor.

## Dimensions

Dimensioni esterne	2227x940x1224 mm
--------------------	------------------

## Technical data

Alimentazione	Electric
Assorbimento a regime (dotazione standard)	0.61 kW
Assorbimento all'avviamento (dotazione standard)	0.66 kW
Classe climatica	3
Frequenza	50 Hz
Gas refrigerante	R452A
Potenza assorbita dall'illuminazione (dotazione standard)	0.023 kW
Potenza assorbita dall'illuminazione (mensola intermedia)	0.023 kW
Refrigerazione	ventilated
Superficie espositiva	1.66 Mq
Temperatura d'esercizio	+2 +6 °C
Voltaggio	220 V, 240 V