

Cod: 112630060242857

Refrigerated pastry counter straight glazing ventilated with intermediate shelf white +2 +6 °C 180,2x94x122,4h cm



Description

Strengths: - Technology, design and production 'Made in Italy';- Compact dimensions (depth of only 945 mm);- Ideal for any type of environment;- Low energy consumption and low environmental impact;- Stainless steel work and display surface;- Easily removable stainless steel display trays to guarantee easy cleaning of the display case;- Easily removable and customisable front and side finishes;- Hot air glass anti-fogging system;- White pre-painted sheet metal tub (suitable for food contact with high-pressure injected polyurethane insulation without environmentally hazardous CFC gas for the environment (density 40 Kg / m³);- Can be ducted;- Easy and immediate installation.- Sheet metal side panels with tempered glass sides;- Electronic control panel;- Ceiling lamp with LED lighting;- 2 open compartments, complete with intermediate shelf;- 1 intermediate shelf in tempered glass;- Condensate evaporator tray equipped with PTC resistor.

Dimensions

Dimensioni esterne	1802x940x1224 mm
--------------------	------------------

Technical data

Alimentazione	Electric
Assorbimento a regime (dotazione standard)	0.61 kW
Assorbimento all'avviamento (dotazione standard)	0.65 kW
Classe climatica	3
Frequenza	50 Hz
Gas refrigerante	R452A
Potenza assorbita dall'illuminazione (dotazione standard)	0.016 kW
Potenza assorbita dall'illuminazione (mensola intermedia)	0.016 kW
Refrigerazione	ventilated
Superficie espositiva	1.33 Mq
Temperatura d'esercizio	+2 +6 °C
Voltaggio	220 V, 240 V