

Cod: 112630360242858

**Refrigerated pastry counter straight glazing ventilated with blue intermediate shelf +2 +6 °C 222,7x94x122,4h cm**



## Description

Strengths: - Technology, design and production 'Made in Italy';- Compact dimensions (depth of only 945 mm);- Ideal for any type of environment;- Low energy consumption and low environmental impact;- Stainless steel work and display surface;- Easily removable stainless steel display trays to guarantee easy cleaning of the display case;- Easily removable and customisable front and side finishes;- Hot air glass anti-fogging system;- White pre-painted sheet metal tub (suitable for food contact with high-pressure injected polyurethane insulation without environmentally hazardous CFC gas for the environment (density 40 Kg / m<sup>3</sup>);- Can be ducted;- Easy and immediate installation.- Sheet metal side panels with tempered glass sides;- Electronic control panel;- Ceiling lamp with LED lighting;- 2 open compartments, complete with intermediate shelf;- 1 intermediate shelf in tempered glass;- Condensate evaporator tray equipped with PTC resistor.

## Dimensions

|                    |                  |
|--------------------|------------------|
| Dimensioni esterne | 2227x940x1224 mm |
|--------------------|------------------|

## Technical data

|                                                           |              |
|-----------------------------------------------------------|--------------|
| Alimentazione                                             | Electric     |
| Assorbimento a regime (dotazione standard)                | 0.61 kW      |
| Assorbimento all'avviamento (dotazione standard)          | 0.66 kW      |
| Classe climatica                                          | 3            |
| Frequenza                                                 | 50 Hz        |
| Gas refrigerante                                          | R452A        |
| Potenza assorbita dall'illuminazione (dotazione standard) | 0.023 kW     |
| Potenza assorbita dall'illuminazione (mensola intermedia) | 0.023 kW     |
| Refrigerazione                                            | ventilated   |
| Superficie espositiva                                     | 1.66 Mq      |
| Temperatura d'esercizio                                   | +2 +6 °C     |
| Voltaggio                                                 | 220 V, 240 V |