

Cod: 87090708

Curved glass refrigerated display case 631 lt 0+8°C 1700x750x1350 h mm



Description

Ristoattrezzature's professional refrigerated display case, built in AISI 430 stainless steel with AISI 304 stainless steel profiles, is a machine designed to meet the needs of pastry shops, supermarkets, snack bars, sushi bars and all those activities that need to serve their customers cold gastronomic products such as sandwiches, ready-made salads, fruit salads, pastries and cakes, sushi and much more. The ventilated cold display case with internal LED lighting and 600 litre capacity, is equipped with three adjustable internal shelves and curved panoramic glass panes to enhance the display space inside: the glass has a double layer of tempered glass so that the positive temperature, adjustable between 0 and +8°C, is effectively maintained by means of a digital device. The rear double-glazed door is sliding and makes opening and closing the display equipment very convenient. Commissioning the refrigerated display case Before putting the machine into operation, following delivery, we recommend that you keep it switched off for at least 6 hours, switch it on and wait until the desired temperature is reached, only then place the food and drinks inside. What is refrigeration? Refrigeration is a method of food preservation that involves keeping products at a low temperature, without freezing the water inside the food. To do this, food is kept at a temperature of between 0°C and 10°C. In addition to temperature, the storage environment must also be taken into account, especially humidity: an unsuitable

environment can lead to unpleasant consequences such as: loss of product characteristics, development of harmful micro-organisms, withering or browning. Keeping appliance spaces perfectly clean will ensure proper air circulation inside the cells or walls, which is essential for the machinery to function properly.

Dimensions

Dimensioni esterne	1700x750x1350 mm
--------------------	------------------

Technical data

Alimentazione	Electric
Amperaggio	5 A
Capacità	631 Lt
Classe energetica	D
Compressore	secop dle12.6mn
Frequenza	50 Hz
Gas refrigerante	R290
Peso	255 kg
Potenza Elettrica	0.95 kW
Refrigerazione	ventilated
Ripiani	3 Nr
Temperatura d'esercizio	0 +8 °C
Termostato	dixell/carel
Voltaggio	230 V

Standard equipment

In dotazione	3 Griglie totali
--------------	------------------