

Cod: 113570010242857

**Refrigerated pastry counter straight glasses ventilated remote motor and intermediate shelf red +2 +6 °C 180.2x94x122.4h cm**



## Description

Strengths:

- Technology, design and production 'Made in Italy';
- Compact dimensions (depth of only 945 mm);
- Ideal for any type of environment;
- Low energy consumption and low environmental impact;
- Stainless steel work and display surface;
- Easily removable stainless steel display trays to guarantee easy cleaning of the display case;
- Easily removable and customisable front and side finishes;
- Hot air glass anti-fogging system;
- White pre-painted sheet metal tub (suitable for food contact with high-pressure injected polyurethane insulation without environmentally hazardous CFC gas for the environment (density 40 Kg / m<sup>3</sup>);
- Can be ducted;

- Easy and immediate installation.
- Sheet metal side panels with tempered glass sides;
- Electronic control panel;
- Ceiling lamp with LED lighting;
- 2 open compartments, complete with intermediate shelf;
- 1 intermediate shelf in tempered glass;
- Condensate evaporator tray equipped with PTC resistor.

## Dimensions

Dimensioni esterne	1802x940x1224 mm
--------------------	------------------

## Technical data

Alimentazione	Electric
Assorbimento elettrico (dotazione standard)	0.020 kW
Classe climatica	3
Frequenza	50 Hz
Gas refrigerante	R452A
Potenza assorbita dall'illuminazione (dotazione standard)	0.016 kW
Potenza assorbita dall'illuminazione (mensola intermedia)	0.016 kW
Potenza frigorifera	0.83 kW
Refrigerazione	ventilated
Superficie espositiva	1.33 Mq
Temperatura d'esercizio	+2 +6 °C
Voltaggio	220 V, 240 V