

Cod: 113570060242857

Refrigerated pastry counter straight glasses ventilated remote motor and intermediate shelf white +2 +6 °C 180,2x94x122,4h cm



Description

Strengths: - Technology, design and production 'Made in Italy';- Compact dimensions (depth of only 945 mm);- Ideal for any type of environment;- Low energy consumption and low environmental impact;- Stainless steel work and display surface;- Easily removable stainless steel display trays to guarantee easy cleaning of the display case;- Easily removable and customisable front and side finishes;- Hot air glass anti-fogging system;- White pre-painted sheet metal tub (suitable for food contact with high-pressure injected polyurethane insulation without environmentally hazardous CFC gas for the environment (density 40 Kg / m³);- Can be ducted;- Easy and immediate installation.- Sheet metal side panels with tempered glass sides;- Electronic control panel;- Ceiling lamp with LED lighting;- 2 open compartments, complete with intermediate shelf;- 1 intermediate shelf in tempered glass;- Condensate evaporator tray equipped with PTC resistor.

Dimensions

| | |
|--------------------|------------------|
| Dimensioni esterne | 1802x940x1224 mm |
|--------------------|------------------|

Technical data

| | |
|---|--------------|
| Alimentazione | Electric |
| Assorbimento elettrico (dotazione standard) | 0.020 kW |
| Classe climatica | 3 |
| Frequenza | 50 Hz |
| Gas refrigerante | R452A |
| Potenza assorbita dall'illuminazione (dotazione standard) | 0.016 kW |
| Potenza assorbita dall'illuminazione (mensola intermedia) | 0.016 kW |
| Potenza frigorifera | 0.83 kW |
| Refrigerazione | ventilated |
| Superficie espositiva | 1.33 Mq |
| Temperatura d'esercizio | +2 +6 °C |
| Voltaggio | 220 V, 240 V |