

Cod: 11443002016

## Combined electric oven 7 GN 1/1 steam convection trays with Touch Screen controls - AT



### Description

Strong points:

- Humidity control with automatic steam retention/exhaust system;
- Low-emission tempered triple-glazed door. Easy to clean;
- 10" HD capacitive heat-insulated display with simple, intuitive graphics;
- Hinge made entirely of stainless steel. Excellent materials, long life;
- Wifi connection with remote monitoring and diagnostics via iOS/Android app;
- Programmable automatic washing system with integrated detergent and rinse aid tanks; Retractable shower included;

- Smart Cooking function that continuously and automatically monitors the cooking chamber ensuring the highest level of performance;
- Full control of cooking modes: manual cooking, core probe cooking, timed cooking, delta T cooking, cooking and holding;
- Maximisation of energy saving and absolute temperature uniformity in the cooking chamber;
- Each motor has an integrated encoder with speed differential monitoring and capacitive fault control; Fans with 8 speeds and integrated reverse function;
- Possibility of synchronising the start or end times of all baking pans;
- Core probe with 4 detection points for optimised baking monitoring;
- User Friendly recipe book. Possibility to select predefined recipes and/or enter your own;
- The high degree of insulation of the cooking chamber and chimney, combined with the adoption and engineering of advanced fans for heat extraction, and superior quality components, allow all the cooking components to be preserved. superior quality components make it possible to preserve all oven models from damage caused by high temperatures, guaranteeing efficiency and longevity never achieved before.

## Dimensions

Dimensioni esterne	786x870x888 mm
Dimensioni imballo	870x970x1030 mm
Distanza teglie	68 mm

## Technical data

Alimentazione	Electric
Amperaggio	26 A
Capacità camera	100 litres
Capacità di carico teglia	18 Kg
Capacità teglie	7 gn 1/1
Carico massimo	126 Kg
Frequenza	50/60 Hz
Indice di protezione acqua	ipx4
Peso lordo	154.4 kg
Peso netto	120.8 kg
Potenza nominale	13.1/15.5 kW

Pressione	2 - 3 bar
Temperatura d'esercizio	+30 +260 °C
Voltaggio	380 V, 415 V

### **Standard equipment**

In dotazione	Sistema di lavaggio e Sonda al cuore multipunto
--------------	---