

Cod: 11579063007001

Stainless steel refrigerated cabinet 1 door 700 l 0 +8 °C ventilated monobloc - FC



Description

Ventilated refrigeration - built-in unit - evaporator positioned concealed so as to have maximum space available - motor compartment with insulated sides - electronic temperature control with digital thermostat - electric heater around the door frame to eliminate condensation - automatic defrosting - electronic control of defrosting temperature - automatic evaporation of condensation water - anti-corrosion treated evaporator. Door with return spring and reversible (except G-GNV600DT) - door lock with key - door gasket removable without tools - internal LED light - bottom with rounded corners - external bottom and back panels in galvanised sheet metal. Height-adjustable feet. M-GN models are equipped with Monobloc refrigerating unit - plug-in system refrigerating unit characterised by easy and immediate installation or eventual removal/replacement - quieter motor - Monobloc protected by stainless steel sheet.

Dimensions

Dimensioni esterne	740x830x2010 mm
Dimensioni imballo	765x855x2080 mm
Dimensioni interne	620x700x1396 mm
Spessore coibentazione	60 mm

Technical data

Alimentazione	Electric
Capacità	700 Lt
Capacità netta	650 Lt
Classe energetica	D
Frequenza	50 Hz
Gas refrigerante	R290
Materiale	stainless steel
Peso lordo	123 kg
Peso netto	108 kg
Potenza Elettrica	0.305 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura ambiente massima	38 °C
Temperatura d'esercizio	0 +8 °C
Voltaggio	230 V

Standard equipment

In dotazione	3 griglie GN2/1 e 3 coppie di guide
--------------	-------------------------------------