

Cod: 11579063012001

## Stainless steel refrigerated freezer cabinet 1 door 700 l -18 -22 °C ventilated monobloc - FC



### Description

Ventilated refrigeration - built-in unit - evaporator positioned concealed so as to have maximum space available - motor compartment with insulated sides - electronic temperature control with digital thermostat - electric heater around the door frame to eliminate condensation - automatic defrosting - electronic control of defrosting temperature - automatic evaporation of condensation water - anti-corrosion treated evaporator. Door with return spring and reversible (except G-GNV600DT) - door lock with key - door gasket removable without tools - internal LED light - bottom with rounded corners - external bottom and back panels in galvanised sheet metal. Height-adjustable feet. M-GN models are equipped with Monobloc refrigerating unit - plug-in system refrigerating unit characterised by easy and immediate installation or eventual removal/replacement - quieter motor - Monobloc protected by stainless steel sheet.

### Dimensions

Dimensioni esterne	740x830x2010 mm
Dimensioni imballo	765x855x2080 mm
Dimensioni interne	620x700x1396 mm
Spessore coibentazione	60 mm

### Technical data

Alimentazione	Electric
Capacità	700 Lt
Capacità netta	650 Lt
Classe energetica	E
Frequenza	50 Hz
Gas refrigerante	R290
Materiale	stainless steel
Peso lordo	129 kg
Peso netto	114 kg
Potenza Elettrica	0.52 kW
Refrigerazione	ventilated
Sbrinamento	automatic
Temperatura ambiente massima	38 °C
Temperatura d'esercizio	-18 -22 °C
Voltaggio	230 V

### Standard equipment

In dotazione	3 griglie GN2/1 e 3 coppie di guide
--------------	-------------------------------------