

Cod: 115800030023014

**Three-phase basket washer production 67-100 baskets now 118x83x143h cm**



## **Description**

Compact model. Specially designed for small spaces.  
2 speeds.

Stainless steel construction

Stainless steel central feed equipped with a torque limiter by means of a clutch in case of blockage.

Separation of the various zones by intermediate screens.

Automatic start.

Economy

Flush economiser.

Pressure reducer for rinsing water quantity regulation.

Programmed automatic stops in case of no load.

Feed stop and timing by activating the limit switch.

## Cleaning and maintenance

Large assisted opening door, allowing access for cleaning and checks.

Hoses and nozzles easily removed for cleaning.

Stainless steel filters.

Easy boiler draining by releasing the tube.

Easy fault detection via indicator lights.

Easy repair without removing the machine.

## Washing

Washing hoses with recessed stainless steel nozzles.

Highly efficient and durable wear-free nozzles.

Powerful wash pump in vertical position allowing self-draining.

Easy installation of dosing unit, with pre-set inlet in the tank. Rinse

Removable rinsing pipes with stainless steel diffusers with great diffusing power.

Automatic boiler filling without risk of resistor failure.

Temperature control with high-precision probes.

Display and adjustment of wash and rinse temperatures on the digital display at the push of a button.

Easy installation of the dispenser, with pre-set inlet in the boiler.

## Dimensions

Altezza utile	400 mm
Dimensioni cesto	500x500 mm
Dimensioni esterne	1180x830x1430 mm

## Technical data

Alimentazione	Electric
Capacità caldaia	20 Lt
Frequenza	50 Hz
Peso netto	200 kg
Potenza pompa	1.5 kW
Voltaggio	400 V